

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR.
(Other instruction.
verse side)DATE
on re-Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
0000064

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME Grier
2. NAME OF OPERATOR Anadarko Production Company	8. FARM OR LEASE NAME Grier
3. ADDRESS OF OPERATOR P. O. Box 116, Lordsburg, New Mexico	9. WELL NO. 5
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL & 1900' FNL of sec. 31, Twp 16S, R 31E.	10. FIELD AND POOL, OR WILDCAT Square Lake
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 31 16S 31E	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set liner, perf, & frac.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Start workover on Sept 8, 1968. Back off safety joint. Lost off stuck tbg. Drill new 6 1/4" hole from 3206' to 3121'. 100 sks of class. cement 1/2" - 2" - 0, 1 at annul. 2nd, 13 & 14 ft. into annul. Ran 400' of 6 1/4" of liner. Top of liner 2933'. Drilled 97' of cement out of csg with 6 1/4" bit. Drilled 20' of cement out of liner w/3 7/8" bit. Perforate w/Densijet from 3311'-03' w/16 holes, 3190'-80' w/20 holes, 3142'-36' w/6 holes, & from 3132'-29' w/2 holes. Ran 3 straddle pkrs. Frac perfs 3311'-29' w/10,000 gals brine water + 25 gals Calgon scale inhib. + 6500# of sand @ a max. treating press. of 5200#. Frac perfs 3190'-80' w/10,000 gals brine water + 50 gals of Calgon + 10,500# of sand @ a max. treating press. of 5100#. Frac perfs 3142'-36' & 3132'-29' w/10,000 gals brine water + 25 gals Calgon + 10,000# of sand @ a max. treating press. of 4900#. Shut in overnight. Ran 3 7/8" bit & circ. hole cln. Ran tbg & rods. Finished workover on Sept 13, 1968.

RECEIVED
SEP 30 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

SEP 30 1968

R. L. BUSHMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.