

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FE	
FILE	
J.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

NOV 14 1972

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-2721

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name East Square Lake
2. Name of Operator Newmont Oil Company	8. Farm or Lease Name State "R"
3. Address of Operator P. O. Box 1305, Artesia, New Mexico 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>16S</u> RANGE <u>31E</u> NMPM.	10. Field and Pool, or Wildcat Square Lake G. SA
15. Elevation (Show whether DF, RT, GR, etc.) 3893' G.L.	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

10-19-72: This well was plugged in the following manner:

1. Set bridge plug @ *1512' and mudded hole to surface with 9.5#/gal. mud.
2. Perforated with 3 shots @ *1500'.
3. Ran cement retainer on 2 3/8" tubing to *1462' and pumped in 35 sack cement plug - leaving cement plug from perforations to retainer.
4. Perforated with 3 shots @ 640'.
5. Ran cement retainer on 2 3/8" tubing to 550' and circulated surface pipe then pumped 100 sack cement plug - leaving cement plug from perforations to retainer.
6. Set marker in 10 sack cement plug at top of 5 1/2" casing.

*Note: Unable to set bridge plug lower due to bad place in pipe. Mr. Bill Gressett notified, and verbal approval given to change depths @ 10:30 AM 10/19/72.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Charles C. Joy</u>	TITLE <u>Dist. Supt.</u>	DATE <u>11/9/72</u>
APPROVED BY <u>Lester McNamee</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>SEP 19 1973</u>
CONDITIONS OF APPROVAL, IF ANY:		

posted
O & G
9-21-73