orm 9–331 May 1963)	UNITED STATES M. S). (QIIIIA) IN TWO WAS NOT TO LINE	Form approved.
DEPARTI	MEN OF THE INTERI	OR (Other instructions r	5. LEASE DESIGNATION AND SERIAL NO.
	SEOLOGICAL SURVEY		LC 029438 (A) 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOT	ICES AND REPORTS C	ON WELLS	O. IP INDIAN, ADDOTTED OR TRIBE NAME
Use "APPLICA	tals to drill or to deepen or plug by	PECEIVED	
OIL GAS WELL OTHER	т.А.		7. UNIT AGREEMENT NAME
NAME OF OPERATOR		APR 1.5 1975	8. FARM OR LEASE NAME.
Arwood Ltd.			Carper Johnson A
ADDRESS OF OPERATOR Petroleum Building-	Tower Suite Poswa	D. C.C.	9. WELL NO.
LOCATION OF WELL (Report location c See also space 17 below.)	learly and in accordance with any	State requirements.*	10. FIELD AND POOL, OR WILDCAT
At surface 660 FSL and 1980 FWL			Grb, Jackson, Queen SA
oou FSL and 1980	ŧ.MT		11. SEC., T., R., M., OR BLK. AND- SURVEY OR ARMA
			Sec. 35, T16S,R31E
4. PERMIT NO.	15. ELEVATIONS (Show whether Dr.		12. COUNTY OR PARISH 13. STATE
	Approx. 403	00 G.L.	Eddy
3. Check Ap	propriate Box To Indicate N	ature of Notice, Report, or	Other Data 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
NOTICE OF INTEN	TION TO:	SUBSE	QUENT REPORT OF 1
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
	CHANGE PLANS		가 가 그 모든 보고 를 만든 [중
(Other)			ts of multiple completion on Well
7. DESCRIBE PROPOSED OR COMPLETED OPE proposed work. If we'll is direction nent to this work.) *	many dimed, give subsuitace locali	(Note: Report result Completion or Recom details, and give pertinent date ons and measured and true verti	pletion Report and Log form.) s, including estimated date of starting any cal depths for all markers and zones perti-
7. DESCRIBE PROPOSED OR COMPLETED OPE proposed work. If we'l is direction nent to this work.)* 8 1/4", 24# s 6-30-67 200 s 1) Check free-point 2) Spot 100' plug a 3) Spot 100' plug a 4) Check free-point 100' plug across	set at 746' with 5 sx. plug pumped do and shoot-off 6 across base of salacross shoe joint on 8 5/8" (?) cs	(Note: Report result Completion or Recom details, and give pertinent date ons and measured and true vertically consumed to the surface casing of surface casing are marker.	s, including estimated date of starting and collection starting and collection starting and collections and depths for all markers and zones pertiable to the first of the fir
7. DESCRIBE PROPOSED OR COMPLETED OPE proposed work. If we'l is direction nent to this work.)* 8 1/4", 24# s 6-30-67 200 s 1) Check free-point 2) Spot 100' plug a 3) Spot 100' plug a 4) Check free-point 100' plug across	set at 746' with 5 sx. plug pumped do and shoot-off 6 across base of salacross shoe joint on 8 5/8" (?) cs stub. True and correct	(Note: Report result Completion or Recom details, and give pertinent date ons and measured and true vertical solutions are sured and true vertical solutions. Applications of the surface casing of the surface marker. REC APPRILED APPRILE	pletton Report and Log form) s, including estimated date of starting and call depths for all markers and zones perturbed to the second depths for all markers and zo
8 1/4", 24# s 6-30-67 200 s 1) Check free-point 2) Spot 100' plug a 3) Spot 100' plug a 4) Check free-point 100' plug across 5) Spot 25' plug at	set at 746' with 5 sx. plug pumped do and shoot-off 6 across base of salacross shoe joint on 8 5/8" (?) cs stub. True and correct	(Note: Report result Completion or Recom details, and give pertinent date ons and measured and true vertically consumed to the surface casing of surface casing are marker.	pletton Report and Log form) s, including estimated date of starting any call depths for all markers and zones pertially and depths and depths for all markers and zones pertially and depths for all markers and zones pertially and depths and depths and depths
8 1/4", 24# s 6-30-67 200 s 1) Check free-point 2) Spot 100' plug a 3) Spot 100' plug a 4) Check free-point 100' plug across 5) Spot 25' plug at 8. I hereby certify that the foregoing is SIGNRO . San	set at 746' with 5 sx. plug pumped do and shoot-off 6 across base of salacross shoe joint on 8 5/8" (?) cs stub. surface and surf	(Note: Report result Completion or Recom details, and give pertinent date ons and measured and true vertical solutions are details, and give pertinent date ons and measured and true vertical solutions are details, and give pertinent date on surface and true vertical solutions and measured and true vertical solutions and true vertical s	pletton Report and Log form) s, including estimated date of starting and call depths for all markers and zones perturbed of the first starting and call depths for all markers and zones perturbed of the starting of the sta
8 1/4", 24# s 6-30-67 200 s 1) Check free-point 2) Spot 100' plug a 3) Spot 100' plug a 4) Check free-point 100' plug across 5) Spot 25' plug at 8. I hereby certify that the foregoing is SIGNRO	set at 746' with 5 sx. plug pumped do and shoot-off 6 across base of salacross shoe joint on 8 5/8" (?) cs stub. surface and surf	(Note: Report result Completion or Recom details, and give pertinent date ons and measured and true vertical solutions and measured and true vertical solutions. Solution with the solution of the surface casing of surface casing if 8 5/8" pure face marker. REC APR U. C. GEOLG ANTESIA, I.	pletton Report and Log form) s, including estimated date of starting any call depths for all markers and zones pertiable of the starting any call depths for all markers and zones pertiable of the starting any call depths for all markers and zones pertiable of the starting and the starting and the starting and the starting and the starting of the s

See Instructions on Reverse Side

CONTACT THIS OFFICE REGARDING ABOYE BEFORE MAKING FINAL CLEANUP.