

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

N. M. O. C. C. COPY

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Copy to SF  
Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 056302 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Kennedy-Johnson A

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Gbr. Jackson, Queen S.A.

11. SEC., T., R., N., OR BLK. AND  
SURVEY OR AREA

Sec. 35, T16S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well  
2. NAME OF OPERATOR  
Arwood Ltd.  
3. ADDRESS OF OPERATOR  
Petroleum Building, Tower Suite, Roswell, N. M. 88201  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface  
1980' FNL and 660' FWL Sec. 35

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4052 G.L. 4062 D.F.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☒  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

12 1/2" @ 56' w/ sacks.

7" @ 3448' with 378 sacks. Stage Collar @ 891' with 150 sacks.

1) Set a cast iron bridge plug @ +/- 3400'. Spot minimum of 35' of cement on top of bridge plug with dump bailer.

2) Spot 100' plug across base of salt at 1870'.

3) Spot 25' plug at surface and marker.

Mud- (25 lbs. gel/bbl.) will be utilized between all plugs.

RECEIVED

APR 28 1975

O. C. C.  
ARTESIA, OFFICE

RECEIVED

U.S. DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

18. I hereby certify that the foregoing is true and correct

SIGNED

*J. M. Bay*

TITLE

*Agent*

DATE 4/22/75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side