



County Eddy Depth 4500' Pool Robinson*

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company J. D. Hancock Oil Co., LTD. Well No 1 Lease Continental-State

660' Feet from N. Line 1980' Feet from W. Line, Sec. 36 Twp. 16S Rge. 31E

Land State Contractor The Denver Company

T. A 280'
T. X 1275
B. X
T. Del Li
T. Del Sd
T. Y
T. SR
T. Q
T. PR
T. GB
T. SA 2800
T. Glo
T. Blby
T. CF

Elevation 4152 Spudded 5-12-55 Completed 7-6-55

T. Tu Total Depth 4025 P.B. 2912
T. Full Top Pay District 6
T. DR I.P. BOPD
T. Wich A. Base on BO Hrs.
T. Abo Choke: Inch
T. WC Tubing @ Ft.
T. Hu Press: Tbg. Csg.
T. Per-Fe GCR Gravity
T. Penn Effective Perfs.:
T. Strawn
T. Miss
T. WF

CSG. & CEMENTING RECORD		
Size	Feet	Sax Cement
<u>2 1/2</u>	<u>30</u>	<u>10</u>
<u>2 7/8</u>	<u>727</u>	<u>250</u>
<u>3 1/2</u>	<u>1002</u>	<u>145</u>

T. Dev Acid, Frac & Shooting Record:
T. Sil From To
T. Fuss From To
T. Mon From To
T. Simp From To
T. McK
T. Ell
T. G.M.
T. Gr SHOWS
T. S/
T. S/
T. S/
T. S/
T. S/
T. S/

May 11, 1955	Loc	
	<u>3-50 x 12. Minn</u>	<u>✓ 3700-4000, 100-50'</u>
<u>4-25</u>	<u>4 2800 anby</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 3500-4000</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 4000-4200</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 4500-4700</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 5000-5200</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 5500-5700</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 6000-6200</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 6500-6700</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 7000-7200</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 7500-7700</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 8000-8200</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 8500-8700</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 9000-9200</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 9500-9700</u>	<u>✓ 4000-4200, 100-50'</u>
	<u>4 10000-10200</u>	<u>✓ 4000-4200, 100-50'</u>

TD 4085 solo was on up for
perf 40h 4046-56, 40h 4058-68
to 500 R/A + repeat 30h 4046-56
30h 4058-68 + to 1000 R/A +

subd 17 16 a/w + xw 24 hrs. set
RND 4026, 29 all parts w/ 500 saf.

TD 4085 solo R12 4026 prep fine,
perf 48h 3956-3978 to w/ 500 R/A

+ subd 92 F 9 hrs cut 60% oil 40% a/w
Actu 5000 R/A + subd 16 BC + 40% a/w b₁¹
+ subd dry.

TD 4085 solo R12 3912 subd
perf 16h 3832-51 to w/ 300 R/A

+ subd load + a/w, silica-
5000 + 5000 # perf 3832-51
subd load + 2 dry

36 h 3796-3805 oil 4000 + 6000

TD 4085 solo, R12 3912 sub,
2" 3950 + oil 2 days + subd
11.6 12 L.C + 3/4 B x w 2 hrs.

✓ TD 4085 solo BB 3912 SI

✓✓