



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office L.S.
Lease No. 068677
Unit D

30-015-05906

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|-------------------------------------|--|--|
| NOTICE OF INTENTION TO DRILL | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 17, 1957

Davis-Ped.

Well No. 12-W is located 1310 ft. from N line and 1310 ft. from E line of sec. 16

N/4, E/4 15

16S

29E

R 10N

High Lonesome

Eddy

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 3701 ft. G.L. 3694.5

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Drill 12 1/2" hole to 136' Set 8 5/8", 360 S.H. casing cement with 100sx. Drill 7 5/8" hole to T.D. approx 1950' Set 4 1/2" BCW 9.5# New casing on bottom, cement with 600sx to circulate to surface perforate Queen pay section and complete as a water injection well for pilot water flood in compliance with the Oil Cons. Comm. order R-975

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Hoab Drilling Co.

Address Box 1268

Artesia, New Mexico

By Archie M. Spier

Title Prod. Supt.