

APPROVED

JUN 10 1963

RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office
Lease No. **NM05126**
Unit**RECEIVED**

JUN 11 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Roswell, N. Mex. **June 5**, 19 **63**

Yates-Federal **660** ft. from **N** line and **1505** ft. from **E** line of sec. **30**

NE/4 NW/4 **16S** **29E** **NM PM**

($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat **Eddy** **New Mexico**

(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **3670** ft.**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well drilled to 325 feet in salt. Run 9 joints Rg. 3
 8 5/8"-24# Used surface casing set @ 325 feet.
 Cemented 50 sacks Rg plus 1 sack calcium chloride
 W. O. C. 24 hrs. drilled out tested-water shut off
 Drilling ahead.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

T. J. Wolfelt
 Company
 Address **c/o McCOY & STEVENS**
606 Security Nat'l. Bldg. Bldg.
Roswell, New Mexico

By **W. A. McCoy**
 Title **Agent**