

SANTA FE, NEW MEXICO 87501

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

DEC 16 1981

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
647	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input checked="" type="checkbox"/> Injector		7. Unit Agreement Name Artesia Unit
2. Name of Operator DEPCO, Inc.		8. Farm or Lease Name Artesia Unit
3. Address of Operator 800 Central, Odessa, Texas 79761		9. Well No. 6
4. Location of Well UNIT LETTER M, 330 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 17s RANGE 28e HMPM.		10. Field and Pool, or Wildcat Artesia (O.Grb. SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3663 GR		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DEPCO intends to run a retainer to approximately 2150' and squeeze perfs. (2208-14, 2250-58) with approximately 75 sx. cement, then fill hole with mud ladden fluid to approximately 1800'. Run a retainer to approximately 1725' and squeeze perfs. (1781-88) with approximately 75 sx. cement, then fill hole with mud ladden fluid to approximately 1350' and perforate squeeze holes at approximately 1325'. Run a retainer to approximately 1275' and squeeze perfs with approximately 75 sx. cement, then fill hole with mud ladden fluid and set a 10 sx. cement plug at the surface with a dry hole marker.

* Ref e 525' + squeeze w/ 45 SX S
Fill hole on backside of 8 5/8" Csg

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leon Standard Leon Standard TITLE Field Engineer DATE 12-14-81

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE DEC 21 1981

CONDITIONS OF APPROVAL, IF ANY:

Notify N.M.O.C.C. in sufficient time to witness

Plugging

* As Noted Above