

REPORT OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1951 KB feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Production June 28, 1963

GIL WELL: The production during the first 24 hours was 40 barrels of liquid of which 100% was oil 0% was emulsion; 0% water; and 0% was sediment. A.P.I. Gravity 37°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Test String in well

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southwestern New Mexico

Northwestern New Mexico

T. Apache	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
T. Salt	T. Monroya	T. Farmington
T. Yates 377'	T. Simpson	T. Pictured Cliffs
T. Permian 632'	T. McKee	T. Menefee
T. Queen 1200'	T. Ellenburger	T. Point Lookout
T. Gravelly 1617'	T. San Wash	T. Mancos
T. San Andres 1924'	T. Granite	T. Dakota
T. O'Neals	T. Premier 1890'	T. Morrison
T. ...		T. Penn.
T. ...		T.
T. ...		T.
T. ...		T.
T. ...		T.

CATION RECORD

From	To	Formation	From	To	Thickness in Feet	Formation
0	110	110	Lime, sand, red shale			
110	377	267	Anhydrite			
377	450	73	Red sand & anhydrite			
450	632	182	Anhydrite, red shale, dolomite			
632	1200	568	Dolomite & anhydrite			
1200	1245	45	Red sand			
1245	1617	372	Anhydrite, red shale & sand			
1617	1890	273	Dolomite, & sand			
1890	1924	34	Sand & dolomite			
1924	1951	27	Dolomite			

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby certify and affirm that the information furnished herein is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 28, 1963

(Date)

Company or Operator International - Yates Address P.O. Box 427, Artesia, New Mexico
Name [Signature] District Engineer