


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office 77 M.Lease No. 01171-AUnit "E" *ST*NOTE: This well within the "Little Lucky Lake Unit"
operated by Texaco, Inc.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	casing test & cement jobs

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3, 1963

Well No. 1 is located 2310 ft. from N line and 660 ft. from W line of sec. 3

Lot 5

(1/4 Sec. and Sec. No.)

16-S

(Twp.)

30-E

(Range)

(Meridian)

West Henshaw

(Field)

Eddy

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3869 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- (1) Set 8 5/8" OD, J-55 csg. at 392 feet. Cemented with 175 sks. 6% gel & 100 sks. of Neat with 2% C.C. Circulated approx. 75 sks. Tested casing before drilling to 850 lbs.
- (2) Set 5 1/2" OD, 14# J-55 csg. at 2839 feet. Cemented with 110 sks. Neat. Tested csg. with 1200 lbs. pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Hiawatha Oil & Gas CompanyAddress 1018 Midland Savings Bldg.Midland, TexasBy Jed B. Sullivan
Title Dist. Supt.