	RECEIVED	6			- Serviced	7/1/86	1 1 1	1 1
TAFE					Port	a (C-1966)		╺┼╌╌┼╴
G. 5	- 2	NE	W MEXICO OI	L CONSERVA	TON COMM	ISSION		┽╌┼
NSPORTER	0iL			nta Fe, New M				
RATION OFFICE	GA5							
RATOR	<u>_</u>							
(1) 11 M. 1	r I		W	ELL RECC	RD		<b></b>	┿╌┼╴
						<u>+</u> }	-+	╋
M-il A		<b>F</b> O'l G					-+	
later th	an twenty di	ays after compl	ervation Commissio etion of well. Follo	w instructions in l	luics and Regul	ations -		
of the (	Commission.	Submit in QU	INTUPLICATE	If State Land	submit 6 Cop	ies Loca	AREA 640 ACRE	i Ctily
Ma	cCoy and	l Stevens		94 ka 44		Bogle	••••••••••••••••••••••••••••••••••••••	
	1	(Company or Op	errior)			( <b>Lesse</b> )		
Vell No	1	, in		¼, of Sec	, T.	16S R.	31E	, NM
W	Vildcat			Pool,	Eddy			Cou
Vell is	1980		South	line and	1980	feet from	East	
1 SCCHOR		Decembe	orate Land the Oil :	and Gas Lease No. 62	LS	Daamha	· 71	
						December		-
						,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
ddre ss	P, O,	Box 798,	Artesia, Ne	w Mexico		******	*****	
						formation given is to		
		······				tormadon Breen is u	be kept conne	iential t
			<b>,</b>					
			0	IL SANDS OR Z	ones			
io. 1, from.	4022		4032	No. 4	from	to.		
						to.		
o. 3, from	•••••••••••••••••••••••		to	No. 6	from	to.		
			IMPO	<b>BTANT WATER</b>	SANDS			
nclude data	on rate of w	vater inflow and	d elevation to which					
o. 1. from			to	-		6000		
						_	******	
			to				*****************************	••••••••••••••
o. 3, from			<b>t</b> o			feet	******	
o. 4, from			to			feet		
		<del></del>	·····	CASING BECO	RD			
SIZE	WEIGI PER FO			KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURP	067
0 5/00	24		1 400					
<u>8-5/8''</u> 5-1/2''				HAL		4022 20	Surfac	
<u>-114</u>	<u> </u>	New	<u>r 4100</u>	HAL		4032-38	Oil Stri	ng
				<u> </u>				
					NG RECORD			
			MUDDING	AND CEMENT				
SIZE OF	SIZE OF	WHERE	NO. SACKS	METHOD		MUD	AMOUNT O	
HOLE	CASING	SET	NO. SACKS OF CEMENT	Method Used		MUD BAVITY	AMOUNT O MUD USEI	
HOLE	CASING 8-5/8	400	NO. SACKS OF CEMENT 50	METHOD USED Pump & F	lug			
SIZE OF HOLE 11 7-7/8	CASING	SET	NO. SACKS OF CEMENT	Method Used	lug	RAVITY	MUD USEI	
HOLE	CASING 8-5/8	400	NO. SACKS OF CEMENT 50	METHOD USED Pump & F	lug		MUD USEI	
HOLE	CASING 8-5/8	400	NO. SACES OF CEMENT 50 100	Pump & F	lug		MUD USEI	
HOLE	CASING 8-5/8	400	NO. SACES OF CEMENT 50 100	METHOD USED Pump & F	lug		MUD USEI	

# SANDFRAC 30,000 gals lease oil with 30,000 pounds 20/40 sand.

.....

Result of Production Stimulation. Testing

· \_\_

------

Depth Cleaned Out

.....

.....

### RECORD OF DRILL-STEM AND SPECIAL TERMS

If drill-stem or oth	er special (	tests or deviation surveys	were made, submit report on se	parate sheet and attach heret	œ
		TO	ols used		
Rotary tools were used from	0	feet to. 4100	feet, and from	feet to	feet.
Cable tools were used from		feet to	feet, and from	feet to	feet.
		PB	ODUCTION		
Put to Producing	-	, 19	-		

was oil; ......% was emulsion; ......% water; and ......% was sediment. A.P.I. Gravity..... 

liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

## PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

	Southeastern N	Northwestern New Merico			
Т.	Anhy	Т.	Devonian	т.	Ojo Alamo
т.	Salt		Silurian	Т.	Kirtland-Fruitland
<b>B</b> .	Salt	Т.	Montoya	Т.	Farmington
Т.	Yates	Т.	Simpson	T.	Pictured Cliffs
Т.	7 Rivers 2713	Т.	McKee	Т.	Menefee
Т.		Т.	Ellenburger	Т.	Point Lookout
Т.	Grayburg 3697	Т.	Gr. Wash	Т.	Mancos
T.	San Andres. 4074	т.	Granite	Т.	Dakota
Т.	Glorieta	Т.		Т.	Morrison
Т.	Drinkard	Т.		Т.	Penn
Т.	Tubbs	Т.		Τ.	
Т.	Abo	T.		Т.	
Т.	Penn	Т.		Т.	
T.	Miss	Т.		Т.	

### FORMATION RECORD

From	То	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	60	60					
60	480	420	· · · ·				
480	1500	1020	Redbed				
1500	1600	100	Anhydrite				
1600	2500	900	Salt & Grayburg				
2500	3400	900	Anhydrite & Gyp		;		
3400	3800	400	Anhydrite & Lime Lime & Dolomite				
3800	4022	222	Lime & Dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records. V 1

Company or Operator McCoy and	Stevens
-------------------------------	---------

Name. W. G. McCoy

Address 606 Security Nat Posizion as Title. Partner

January 21, 1963

N. M.

Bk. Bldg., Roswell,

### MCCOY AND STEVENS NO. 1 BOGLE DEVIATION DEPTH

- 407' 1/4<sup>0</sup>
- 978' 1/2°
- $1459 1/4^{\circ}$
- $1810 3/4^{\circ}$
- $2370 1 1/2^{\circ}$
- 2828' 1-1/4°
- 2990' 1-1/2°
- 3425' 1-1/2°
- 3725' 1-1/40
- 4100' 1-1/4°

The above information is true and correct to the best of my knowledge.

Subscribed and sworn to before me this 21st day of January, 1963

Notary Public in and for Chaves County, New Mexico

My Commission Expires 12-24-65.

ALCORT FRANCES NEWS NGL I BOOL 9 OTVIATUM DEPOE

The obset follows attact to calcover of correct to the cases of a value get.

M. C. McCar

a see . We should be yet self and a we ended of anows the bar was a

Martin Daries

rotary wubits in and for Chaves Cousty, New Mexico

.EC children and the state of the