

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>J.E. Boddingfield</u>		Lease <u>State</u>		Well # <u>6</u>	
Location of Well	Unit <u>SwSw N</u>	Section <u>36</u>	Township <u>17S</u>	Range <u>27E</u>	County <u>Eddy</u>
Drilling Contractor	<u>D.M. Bassett</u>		Type of Equipment <u>Caldo. tools</u>		

  

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>10"</u>	<u>8 5/8"</u>	<u>22 #</u>	<u>new</u>	<u>1000'</u>	<u>mixed</u>
<u>8"</u>	<u>7"</u>	<u>20 #</u>	<u>used</u>	<u>1400'</u>	<u>Circulated</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by Pipe in hole on arrival date \_\_\_\_\_

Cementing Program

Size of hole 10" + 7 7/8" Size of Casing 7 Sacks cement required \_\_\_\_\_

Type of Shoe used GUIDE Float collar used no Btm 3 jts welded \_\_\_\_\_

TD of hole 1343 Set 1350 Feet of 7 Inch \_\_\_\_\_ # Grade \_\_\_\_\_

New ~~used~~ csg. @ 1350 with 200 sacks neat cement around shoe  
+ \_\_\_\_\_ sax 1340 additives \_\_\_\_\_

Plug down @ 8:10 (AM) (PM) Date 5-4-63

Cement circulated no \* No. of Sacks \_\_\_\_\_

Cemented by DENTON Witnessed by LOBLEY

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ no (AM) (PM) Date will not drill shoe

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks \* Circulation was completed by 50 sks  
put in from top. 5-5-63.