

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	6
FILE	1
U.S.G.S.	2
LAND OFFICE	
TRANSPORTER	
OIL	
GAS	
PRODUCTION OFFICE	
OPERATOR	

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations

Kincaid & Watson Drilling Company If State Land submit Register & Shallow

AREA 640 ACRES
LOCATE WELL CORRECTLY

17 South 25 East
(Lease)

Well No. 1980, in North 1/4 of Sec. 1625, T. 17 S., R. 25 E., NMPM.
Pool, County.

Well is 2-17-28 feet from 9-17 line and 63 feet from 10-2 line
of Section 63. If State Land the Oil and Gas Lease No. is 8-9782

Drilling Commenced Kincaid & Watson Drilling Company 19 Drilling was Completed 19
P.O. Box 498, Artesia, New Mexico

Name of Drilling Contractor 3585

Address

Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until 19.

1564
16151576
1618

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 1335 to 1340 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

RECEIVED

MAR 5 1964

D. C. C.
ARTESIA, OFFICE

CASING RECORD

SIZE OF PIPE	WEIGHT PER FOOT	TYPE OR USED	QUANTITY	TYPE OF JOINT	ADD AND PULLED FROM	None PERFORATIONS	Casing PURPOSE
10 3/4"	25	Used	410	Reg.	None	None	Surface
8 5/8"	20	Used	1389	Reg.	All	None	Water String
7"	14	None	1649	Float	None	1615-1618	Oil String
5 1/2"						1564-1576	

MUDDING AND CEMENTING RECORD

SIZE OF PIPE	WEIGHT PER FOOT	TYPE OR USED	QUANTITY	TYPE OF JOINT	MUD GRAVITY	AMOUNT OF MUD USED
8 5/8"	20	Used	1389	Reg.		
7"	14	None	1649	Float		
5 1/2"						

RECORD OF PRODUCTION AND STIMULATION

Dowell Inc. treated through perforations, 1 hole at 1618, 1 hole at 1615, 48 holes at 1564-76, with 31,000 gallons of lease oil and 55,000 lbs. 20-40 sand.

Natural production was approximately 1 qt. per hour.

After treatment approximately 5 B.O.P.D.
Result of Production Stimulation.

Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1649 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

3-1-64

PRODUCTION

Put to Producing, 19 5 100

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. 115	T. Devonian	T. Ojo Alamo	
T. Salt. 470	T. Silurian	T. Kirtland-Fruitland	
B. Salt	T. Montoya	T. Farmington	
T. Yates. 1335	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	20	20	Red bed				
20	35	15	Red bed and gyp				
35	60	25	Sand				
60	115	55	Gravel, red bed & gyp				
115	308	273	Salt				
308	402	14	Salt & anhydrite				
402	450	48	Anhydrite				
450	470	20	Salt				
470	545	75	Anhydrite				
545	790	245	Anhydrite & red rock				
790	1100	310	Anhydrite				
1100	1250	150	Anhydrite, shale & red rock				
1250	1335	85	Anhydrite				
1335	1352	17	Red sand				
1352	1370	18	Anhydrite				
1370	1387	17	Anhydrite & shale				
1387	1445	58	Anhydrite				
1445	1579	134	Anhydrite, red rock & shale				
1579	1595	16	Sand				
1595	1605	10	Anhydrite				
1605	1625	20	Sand & anhydrite				
1625	1629	24	Anhydrite				
1629	T.D.						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done so far as can be determined from available records.

Kincaid & Watson Drilling Company

Box 496, Artesia, New Mexico

Company or Operator

Address

Name

Position or Title

Assistant Secretary

G. R. Holman