


APPROVE



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. NM 012898
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING <input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 3, 1963

Well No. 2 is located 160 ft. from [N] line and 550 ft. from [E] line of sec. 11
N 1/4 34 1/4 S 11 17 23E NM 01
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Vandegriff-Kayes Sidy New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 1543 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run Gamma-neutron log T.O. 1053'. Plugged well back to 1635'. Perforated 1584-1594' with 4 3/4" perforations. Perforated 1616-1628' with 5 3/8" holes, one 3/8" hole at 1633'. Treated with 40,000 gallons of water and 44,000# of sand. Breakdown pressure 2600#. Maximum injection rate of 22 bbls/minute at 2000" pressure. According to tables all holes taking treatment with 600" pressure across each hole.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Kersey & CompanyAddress P. O. Box 316Artesia, New Mexico

By

Harold Kersey

Title

Owner