

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 7
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

1. LEASE DESIGNATION AND SERIAL NO.

SM-01146

2. IF SERIAL, ALLOTMENT OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

Oil Well ☐ Gas Well ☐ OTHER ☒ Drilling Well

3. NAME OF OPERATOR

Leonard Oil Company

4. ADDRESS OF OPERATOR

P.O. Box 400 - Roswell, New Mexico

5. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

Now also space 17 below.

At surface 660' FNL & 660' FWL of Section.

14. PERMIT NO.

15. ELEVATIONS (Show whether 50, 57, 58, etc.)

3725 GR, 3737 KDB

7. UNIT ASSIGNMENT NAME

8. FARM OR LEASE NAME

Fed. Humble

9. WELL NO.

1

10. FIELD AND POOL OR WELLS

Validcat

11. SEC. T. R. W. OR NE. AND SURVEY OR AREA

Sec. 30-T 16S. R 30E

NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TEST

SHOOTING OR ACIDIZING

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

REPAIRING CASING

ABANDONMENT

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. ADDITIONAL INFORMATION OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and names pertinent to this work.)

8-24-64 Spudded @ 3:00 p.m.

8-25-64 Set 48# H-40 13-3/8" casing @ 400'. Cemented w/500 sx regular cement w/2% calcium chloride. Plug down @ 5:00 a.m. After WOC for 18 hours, tested casing w/1000#. Held for 30 minutes, with no drop in pressure. Drilled cement & shoe, tested w/1000# for 30 minutes w/no drop in pressure. Cement job considered satisfactory.

8-26-64 Drilling @ 1901' in anhydrite.

RECEIVED

AUG 31 1964

O. C. C.
ARTESIA, OFFICE

RECEIVED
AUG 28 1964
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE General Manager

DATE 8-27-64

(This space for Federal or State office use)

TITLE

DATE

APPROVED
AUG 28 1964
R. L. BEECHER
ARTESIA DISTRICT ENGINEER

*See Instructions on Reverse Side

