

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 1. LIGATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>dry hole</u>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <u>Exxon Oil Company</u> ✓	8. FARM OR LEASE NAME <u>Exxon Hub</u>
3. ADDRESS OF OPERATOR <u>Box 400 - Roswell, New Mexico</u>	9. WELL NO. <u>1</u>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>on the E. side of Rd. 100 of Sec.</u>	10. FIELD AND POOL, OR WILDCAT <u>Hub</u>
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SUBSEY OR AREA <u>S.30, T.10N, R.30E, N.E.1/4</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>725 GR, 5757 MIB</u>	12. COUNTY OR PARISH <u>McCoy</u>
	13. STATE <u>N. Mex.</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. 9-14 Cement plugs were spotted as follows:

20 in. cement	10,800 - 10,700
20 in. cement	8,900 - 8,800
20 in. cement	7,500 - 7,400
20 in. cement	6,300 - 6,200
20 in. cement	4,200 - 4,100
20 in. cement	2,875 - 2,775

Max-index fluid with a viscosity of 55, weight of 9.1 per gallon and water loss of 9.4 was lost in the interval between cement plugs.

As soon as the rig is removed from the location, the 3-2, 1 which can be recovered with a pump and a cement plug will be placed at the end of the 10-3/8" casing. A regulation marker will be set at the location and the location will be leveled.

RECEIVED

OCT 21 1964

O. C. C.
ARTESIA, OFFICE

RECEIVED
OCT 14 1964
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED: [Signature]

TITLE: General Manager

DATE: Oct. 13, 1964

(This space for Federal or State office use)

APPROVED: [Signature]

TITLE: _____

DATE: _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED
OCT 21 1964
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

