orin 3160-5 Iure 1990)		NITED STATES	FORM APPROVED
	DEPARTMI	ENT OF THE INTERIOR	Budget Bureau No. 1004-0135
	BUREAU OF	F LAND MANAGEMENT	Expires: March 31 1003
	SUNDRY NOTICE	S AND DEDODDE AN A	5. Lease Designation and Serial No. NM-89038
Co not use this	form for proposale to	S AND REPORTS ON WELLS	
	Use "APPLICATION F	drill or to deepen or reentry to a different re OR PERMIT—" for such proposals	servoir.
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation
Vell Gas	Other		
2. Name of Operator MARALO, INC. 3. Address and Telephone No.			8. Well Name and No.
			D.S. "26" FEDERAL #2 9. API Well No.
	MIDLAND, TX 79702		30-015-28719
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			10. Field and Pool, or Exploratory Area
UNIT H, SECTION 26, T20S, R26F			WILDCAT HILLS; SA, EAST
1683' FNL & 12	59' FEL		11. County or Parish, State
CHECK	APPROPRIATE BOX	(S) TO INDICATE MATURE OF	EDDY, NM
TYPE OF	SUBMISSION	(s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA
XX Notice of Intent		TYPE OF A	
Notice o	of Intent	X Abandonment	
C Subara			Change of Plans
Subsequent Report		Plugging Back	New Construction
Final Abandonment Notice		Casing Repair	Won-Routine Fracturing
L Final Abandonment Notice		Altering Casing	· · · · · ·
		Other	Dispose Water
Describe Proposed or Com give subsurface locat	npleted Operations (Clearly state al ions and measured and true vertic	Other	Dispose Water
Describe Proposed or Con give subsurface locat PERFORATIONS: PROPOSED	npleted Operations (Clearly state al ions and measured and true vertic 2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8	Dispose Water (Note: Report results of multiple completion on W. Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sy circid
PERFORATIONS:	2316 - 2324', plugged of 1840 - 1856', open	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8	Dispose Water (Note: Report results of multiple completion on W. Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sy, circ'd
PERFORATIONS: PROPOSED PPERATION: 1. RU plugg	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½"	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/2" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/6 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt.	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dri 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/tbg	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg.	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dri 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/tbg	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg.	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx).	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dri 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ bu 3. TIH w/ bu 5. TIH w/ tbg 6. TIH w/ tbg	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'.	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx).	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dri 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ bu 3. TIH w/ tbg 5. TIH w/ tbg 5. TIH w/ tbg 7. PU and sp 8. Cut off we	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'. 1400'. CIBP and set @ 1400'. 1400'. Spot 100' (20 sx) pot 5 sx cmt plug @ surface ellhead. Clean-up location,	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx).	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dri 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ bu 3. TIH w/ tbg 5. TIH w/ tbg 5. TIH w/ tbg 7. PU and sp 8. Cut off we	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'. 1/2" CIBP and set @ 1400'. 1/2" Spot 100' (20 sx) pot 5 sx cmt plug @ surfac	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx).	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dri 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED PERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/tbg 5. TIH w/ 5 6. TIH w/tbg 7. PU and sp 8. Cut off we hereby certify that the fore gred	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'. to 562'. Spot 100' (20 sx) pot 5 sx cmt plug @ surface ellhead. Clean-up location, egoing is true and correct a Che a Correct	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx).	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cit
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5 6. TIH w/ 5 6. TIH w/ tbg 7. PU and s 8. Cut off we hereby certify that the form gned	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'. g to 562'. Spot 100' (20 sx) pot 5 sx cmt plug @ surfac ellhead. Clean-up location, regoing is true and correct ALLA Cog action tate office use)	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx). I plug from 462 - 562'. Se. , and install dry hole marker. Tide	Dispose Water (Note: Report results of multiple completion on W Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir
PERFORATIONS: PROPOSED OPERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5 6. TIH w/ tbg 7. PU and s 8. Cut off we hereby certify that the form gned	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'. 100' (20 sx) pot 5 sx cmt plug @ surfac ellhead. Clean-up location, proving is true and correct Marked Correct Marked Correct Marked Correct Marked Correct Marked Correct Marked Correct Marked Correct Marked Correct Correc	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD t'. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx). I plug from 462 - 562'. Se. , and install dry hole marker.	Dispose Water (Note: Report results of multiple completion on W. Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir 15.5# @ 2600' w/455 sx. DV @ 1200', cir
PERFORATIONS: PROPOSED PERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5 6. TIH w/ 5 6. TIH w/ tbg 7. PU and s 8. Cut off we hereby certify that the fore gned	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 g open-ended, to PBTD. C ½" CIBP and set @ 1400'. g to 562'. Spot 100' (20 sx) pot 5 sx cmt plug @ surfact ellhead. Clean-up location, regoing is true and correct STREA Cog act tate office use) DAVID R. GLAS	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx). I plug from 462 - 562'. Se. , and install dry hole marker. Tide	Dispose Water (Note: Report results of multiple completion on We Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir
PERFORATIONS: PROPOSED PERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5 6. TIH w/ 5 6. TIH w/ tbg 7. PU and s 8. Cut off we hereby certify that the form gned	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 9 open-ended, to PBTD. C ½" CIBP and set @ 1400'. 9 to 562'. Spot 100' (20 sx) pot 5 sx cmt plug @ surfact ellhead. Clean-up location, regoing is true and correct ULL _ Open- tate office use) DAVID R. GLAN ATTACHED FOR ONS OF APPROV	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx). I plug from 462 - 562'. Se. , and install dry hole marker. Title <u>REGULATORY ANALYST</u> PETROLEUM ENGINEEF	Dispose Water (Note: Report results of multiple completion on W. Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir 15.5# @ 2600' w/455 sx. DV @ 1200', cir Date NOVEMBER 6, 1996
PERFORATIONS: PROPOSED PERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5 6. TIH w/ 5 6. TIH w/ tbg 7. PU and s 8. Cut off we hereby certify that the form gned	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 9 open-ended, to PBTD. C ½" CIBP and set @ 1400'. 9 to 562'. Spot 100' (20 sx) pot 5 sx cmt plug @ surfact ellhead. Clean-up location, regoing is true and correct ULL _ Open- tate office use) DAVID R. GLAN ATTACHED FOR ONS OF APPROV	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx). I plug from 462 - 562'. Se. , and install dry hole marker. Title <u>REGULATORY ANALYST</u> PETROLEUM ENGINEEF	Dispose Water (Note: Report results of multiple completion on W. Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir 15.5# @ 2600' w/455 sx. DV @ 1200', cir Date NOVEMBER 6, 1996
PERFORATIONS: PROPOSED PERATION: 1. RU plugg 2. TIH w/ bu 3. TIH w/ 5 4. TIH w/ tbg 5. TIH w/ 5 6. TIH w/ 5 6. TIH w/ tbg 7. PU and s 8. Cut off we hereby certify that the form gned	2316 - 2324', plugged of 1840 - 1856', open 1445 - 1544', open Plug & Abandon ging unit. TOH w/rods, pu ulldog bailer on sand line a ½" CIBP and set @ 2250 9 open-ended, to PBTD. C ½" CIBP and set @ 1400'. 9 to 562'. Spot 100' (20 sx) pot 5 sx cmt plug @ surfact ellhead. Clean-up location, regoing is true and correct ULL _ Open- tate office use) DAVID R. GLAN ATTACHED FOR ONS OF APPROV	I pertinent details, and give pertinent dates, including estimated date al depths for all markers and zones pertinent to this work.)* f w/ CIBP @ 1920' CASING: 8 5/8 5 ½" mp, and tbg. nd knock out CIBP @ 1920'. Push down hole to TD '. Cap w/ 35' (5 sx) cmt. Firculate hole w/ 10# mud-laden fluid. TOH w/tbg. Cap w/35' cmt (5 sx). Plug from 462 - 562'. Se. , and install dry hole marker. Tide <u>REGULATORY ANALYST</u> PETROLEUM ENGINEEF	Dispose Water (Note: Report results of multiple completion on We Completion or Recompletion Report and Log form of starting any proposed work. If well is directionally dril 3" 24.0# @ 512' w/375 sx, circ'd. 15.5# @ 2600' w/455 sx. DV @ 1200', cir 15.5# @ 2600' w/455 sx. DV @ 1200', cir Date NOVEMBER 6, 1996