

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. NAME OF OPERATOR <i>Am American Petroleum Corp.</i>	3. ADDRESS OF OPERATOR <i>Box 68 Hobbs N.M. 88240</i>	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>1987.43' FSL x 1972.58' FWL, Sec 34, (UNIT K, NE 1/4 SW 1/4)</i>	5. LEASE DESIGNATION AND SERIAL NO. <i>LC-067849</i>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME <i>Malco Holdings "P"</i>	9. WELL NO. <i>1</i>	10. FIELD AND POOL, OR WILDCAT <i>RED LAKE (GSA)</i>	11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA <i>34-17-27 NMPM</i>	12. COUNTY OR PARISH <i>Eddy</i>	13. STATE <i>N.M.</i>
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3571' R.D.B</i>											

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☒
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	
(Other) ☐			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In accordance with Form 9-331 submitted 11/13/64, remedial work performed as follows:

Perforated intervals 1883', 1912', 1921', 1960', 1987', 2060', 2082', 2106', 2118', & 2127' w/1 shot each interval. Acidized with 2000 gallons. Traced w/ 65,000 gal water & 30,000# sand w/other agents.

*Prior to repair, Pmp 14 BO x 0 BW, 24 hours
After " " Pmp 24 BO x 59 BW, 24 hours.*

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL ANY:

5- USGS-ART
1- JWB
1- SUSP
1- ATLANTIC-ROS
1- GSA

Area Supt
APPROVED
DEC 20 1964
H. L. D... ENGINEER
ACTING DISTRICT ENGINEER

DATE

DATE

12-23-64

RECEIVED
DEC 28 1964
GEOLOGICAL SURVEY
ARIZONA NEW MEXICO