

MOCC COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 07781

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LOE FEDERAL

9. WELL NO.

#3

10. FIELD AND POOL, OR WILDCAT

Sq. Lake Gbg-SA

SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

30-16S-31-E

12. COUNTY OR PARISH 13. STATE

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

Injection well

2. NAME OF OPERATOR

ARWOOD, LTD. ✓

3. ADDRESS OF OPERATOR

P. o. Box 64548, Dallas, Texas 75206

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

330 FNL 1998 FW1

RECEIVED

JUN 23 1978

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Work, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON\* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

13" @ 30' w/20 sacks reg.

11" hole to 420', 7 7/8" hole to 3275'.

5 1/2", 15# 0-536' &amp; 3242' to 3274'

5 1/2", 14.4# 536' to 3242' cemented with 150 sx w/4% gel followed by  
150 sx. regular. 50 sx. neat @ 400' with 1" tubing.

## PLUG AND ABANDON

1. Spot a cement plug across perforations 3037-3230.

2. Spot 100' cement across top of salt @ 400'.

3. Spot 25' plug at surface, install marker and cleanup location.  
Gelled mud (25 sx/100 bbls water) between each cement plug.

Plugging witnessed by U.S.G.S. representative.

Lease ready for inspection.

RECEIVED

MAY 24 1978

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

T. M. Boye

(This space for Federal or State office use)

TITLE

Agent

DATE 5/18/78

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACTING DISTRICT ENGINEER

DATE JUN 22 1978

\*See Instructions on Reverse Side

Post p4H  
2102  
6-23-78