

Form 9-331  
(May 1963)

NEW MEXICO STATE COMMISSION  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-060971

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ TA - WIW

OIL &amp; GAS

2. NAME OF OPERATOR

Newmont Oil Company

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

3. ADDRESS OF OPERATOR

P. O. Box 1305, Artesia, N.M. 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

50' FNL &amp; 50' FEL of Sec. 29-16-31

MAR 22 1983

O. C. D.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3980' 3890' GLM

ARTESIA, OFFICE

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/12/82..Pulled tbg and packer, csg parted 1st jt. down, ran 2 7/8" tbg to 3449', pump broke.  
6/15/82..Spotted 50 sack cement plug @ 3449', WOC, ran tbg, tagged plug @ 3359'. Started pumping mud, pump malfunctioned, S.D.  
6/16/82..2 7/8" tbg cemented in hole. Shot 2 7/8" tbg w/jet shot @ 2000'. Pulled tbg. Reported to Peter Chester, U.S.G.S. Roswell.  
6/17/82..Ran tbg w/packer, tested csg to 500 psi, pulled tbg, ran wireline and perf. @ 1650', spotted 50 sack cement, ran tbg and packer to 627' and squeezed cement w/1000 psi.  
6/18/82 Bled well down, tagged plug @ 1580'. Ran wireline and perf. @ 530'. Ran packer to 180' and squeezed 50 sacks cement.  
6/19/82 Plug didn't hold, respotted 40 sack plug, squeezed and SI.  
6/21/82 Plug didn't hold, pumped into formation @ 800 psi squeezed 50 sacks cement, SI.  
6/22/82 Flowing back, squeezed 50 sacks cement @ 400 psi & SI. Waited 7 yrs, opened well, flowed back, squeezed another 50 sacks cement and SI.  
6/23/82 Opened well, pressured up to 1000-psi, held. Tagged plug @ 505'. Spotted 100 sacks cement, circ. 10 sacks to pit, set dry hole marker. Location ready for inspection.

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Area Manager

DATE

9/30/82

(This space for Federal or State office use)

APPROVED BY: PETER CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 18 1983

FOR

JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

Post F 11-2  
3-25-83  
PFA