

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION  
Drawer DD  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
Merit Energy Company

3. Address and Telephone No.  
P. O. Drawer NN, Jal, NM 88252 phone (505)395-2173

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
SEC 24 T-16S R-30E  
660' FSL and 660' FLL

5. Lease Designation and Serial No.

LC-064637-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Henshaw Deep Unit # 14

9. API Well No.

30-015-10573

10. Field and Pool, or Exploratory Area

Henshaw Wolfcamp

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Current Perfs 8656'-8658'<sup>35'</sup> & 8665'-8706' PBDT 8750' Set 4 1/2" CIBP @ 8650' dump bail 20' cement. Displace hole with 9 lb mud to 3046'. Cut 4 1/2" casing @ 3086'. Pump 100' cement which will cover 50' below and 50' above EOC @ 3086'. Displace hole to 503'. Pump 100' of cement which will cover 50' below and above EOC at 503'. Displace hole to 50' of surface with 9 lb mud. Pump 50' surface cement in one 4" dryhole marker so that it is 4' above ground level. Haul off all production equipment, cut off anchors 18" below surface level. Backfill and clean location.

14. I hereby certify that the foregoing is true and correct

Signed Shawn J. Casanova

Title Regulatory Manager

Date 6-7-94

(This space for Federal or State Office Use)

Approved by (ORIG. SGD) JOE G. LARA

Title PETROLEUM ENGINEER

Date 6/28/94

Conditions of approval, if any: Dump bail 35' cement on top of CIBP, tag plug @ 3086', perf 1 squeeze cement @ 503' (plug @ 453-553) and complete w/ attached.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side