

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBJECT OF WELL  
(Name, location,  
year 1966)

WELL NUMBER  
U. S. GEOLOGICAL SURVEY FORM NO. 49-2140A  
NM-074951

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL  GAS WELL  OTHER TA

2. NAME OF OPERATOR  
Shell Oil Company (Western Division)

3. ADDRESS OF OPERATOR  
P. O. Box 1509, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface 660' FNL & 1980' FWL (NE/4 NW/4), Section 25, T-16-S, R-30-E, NMPM Survey, Eddy County, New Mexico

5. PERMIT NO. 16. ELEVATIONS (Show whether SP, ST, OR, etc.)  
3828' DF

7. WELL NAME  
Henshaw Disp Unit

8. FIELD AND POOL, OR WILDCAT  
Henshaw-Wellfield (Wolfcamp)

9. SEC. T. R. M. OR BLM. AND SURVEY OF AREA  
Sec. 25, T-16-S, R-30-E, NMPM

10. COUNTY AND STATE  
Eddy New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDISE
- REPAIR WELL
- (Other)

- FULL OR ALTER CASING
- MULTIPLE COMPLETS
- ABANDON\*
- CHANGE PLANS

- WATER SHUT-OFF
- FRACTURE TREATMENT
- SHOOTING OR ACIDISING
- (Other)

- REPAIRING WELL
- ALTERING CASING
- ABANDONING\*

(Other) Temporarily Abandoned

(Note: Report results of multiple completions as Well Completion or Incompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all marked and zones pertinent to this work.)

March 20 thru April 8, 1966.

1. Perforated 8765' - 8766', 8767' - 8768', 8769' - 8770' w/2-1/2" JSPF.
2. Treated w/500 gallons 15% BDA.
3. Swabbed 99% water.
4. Squeezed perforations 8765' - 8770' w/42 sx. at 5500 psi.
5. Drilled cement 8702' - 8770'. Cleaned out 8770' - 8861' (FWD).
6. Perforated 8764' - 8769' w/2-1/2" JSPF (total 12 holes).
7. Treated w/1000 gallons 15% BDA.
8. Swabbed 75% water.
9. Treated w/2000 gallons 15% NEA.
10. Swabbed 100% water.
11. Shut in April 8, 1966.

RECEIVED

JUN 24 1966

O. C. C.  
ARTESIA, OFFICE

RECEIVED  
JUN 20 1966  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Dell Huber P. W. Huber

TITLE District Production Geologist DATE June 27, 1966

(This space for APPROVAL)

APPROVED BY JUN 21 1966  
CONDITIONS OF APPROVAL, IF ANY:

RUDOLPH C. BAIER, JR.  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side