

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 'PLICATE*
(Other instru. ns on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME 14-08-001-6453 HENSHAW DEEP UNIT
2. NAME OF OPERATOR SHELL OIL COMPANY (WESTERN DIVISION)	8. FARM OR LEASE NAME HENSHAW DEEP UNIT
3. ADDRESS OF OPERATOR P. O. BOX 1509, MIDLAND, TEXAS 79701	9. WELL NO. 16
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FWL (NE/4 NW/4), SECTION 25, T-16-S, R-30-E, NMPM SURVEY, EDDY COUNTY, NEW MEXICO	10. FIELD AND POOL, OR WILDCAT HENSHAW-WOLFCAMP
14. PERMIT NO.	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA SEC. 25, T-16-S, R-30-E NMPM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3828' DF	12. COUNTY DOUGLAS 13. STATE EDDY NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

PLUG BACK ☒

(NOTE: Report results of multiple completion on Well Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DECEMBER 19, 1966 THRU DECEMBER 26, 1966

1. SPOTTED 25 SX CEMENT 8764'-8769' (WOLFCAMP PERFORATIONS).
2. SHOT AND PULLED 7706' OF 5 1/2" CASING.
3. SPOTTED THE FOLLOWING CEMENT PLUGS:
50 SX AT 7705' (TOP OF 5 1/2" CASING STUB).
25 SX 6450'-6550' (TOP OF ABO).
25 SX 4600'-4700' (TOP OF YESO).
50 SX 3400'-3200' (BASE OF SAN ANDRES).
4. COMPLETED PLUGGING BACK DECEMBER 26, 1966.

NOTE: SOLD TO THE RYDER SCOTT COMPANY OF WICHITA FALLS, TEXAS FOR USE AS A WATER INJECTION WELL IN THE LOVINGTON SAND WATERFLOOD.

RECEIVED

JAN 19 1967

O. C. C.
ARTESIA, OFFICE

RECEIVED
JAN 16 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED R. J. DOUBEK

R. J. DOUBEK

TITLE DIVISION MECHANICAL ENGINEER

DATE JANUARY 11, 1967

(This space for Federal or State office use)

APPROVED BY
SIGNATURE OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

JAN 11 1967
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

APPROVED