RECORD COPY

(May 1963)

DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

GEOLOGICAL SURVEY

Form approved. Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

JUL 24 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

1. OIL WELL [X] GAS WELL [ ] OTHER

2. NAME OF OPERATOR: ARWOOD LTD. ✓

3. ADDRESS OF OPERATOR: P.O. BOX 8 LOCO HILLS NM 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface: 660' FNL 1980 FWL

5. LEASE DESIGNATION AND SERIAL NO.: ~~NM 074915~~

6. IF INDIAN, ALLOTTEE OR TRIBE NAME: NM-074951

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: ETZ. FEDERAL

9. WELL NO.: 1

10. FIELD AND POOL, OR WILDCAT: Sq. Lake-Greyburg San Andr

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: 25-16-30

12. COUNTY OR PARISH: EDDY

13. STATE: NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 3820

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[X]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other)			
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

SPOT 250' CEMENT PLUG FROM 3146' TO 2896'
Pump mud from 2896' to 1350'
Pump cement plug 1350' TO 1250'
Pump mud plug from 1250' to 550'
Pump mud plug to 100', fill to surface with cement.
Cleaned surface location and leveled as per U.S.G.S. requirements
Ripped drill pad to a depth of 12"

Posted D-7
P & A
11-7-80

RECEIVED
NOV 03 1980
O. C. D.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED B D Logan TITLE SUPT. DATE 6-13-79

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE ACTING DISTRICT ENGINEER DATE OCT 24 1980

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side