DEPARTM	ED STATES	NN OIL CONS. CO. SSION Draw Could instruction on re- PRESISE SIDE 108 88210	5. LEASE DESIGNATION A LC029424	NO. 42-R1424.
SUNDRY NOTION (Do not use this form for proposa Use "APPLICAT	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
1. OIL GAB WELL OTHER Injection Well CEC 2 1982 2. NAME OF OPERATOR			7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME	
Stallworth Oil & Gas, Inc. O. C. D.			<u>Etz</u> 9. WELL NO.	
B. ADDRESS OF OPERATOR P. O. Box 479, Dallas, TX 75221 ARTESIA, OFFICE			5	
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with any State requirements.</li> <li>See also space 17 below.) At surface</li> </ol>			10. FIELD AND FOOL, OF WILDCAT Square Lake (Grayburg- San Andres)	
10' FSL & 2630' FEL, Section 25, T16S, R30E			11. BEC., T., E., M., OB BLK. AND BUEVEY OF ABEA Sec. 25, T16S, R30E	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF	, RT, GR, etc.)	12. COUNTY OB PARISH	
	3790' GR		Eddy	N. Mex.
16. Check App	propriate Box To Indicate N	lature of Notice, Report, or C	)ther Data	
NOTICE OF INTENTION TO: SUBSEQU			ENT REPORT OF:	
FRACTURE TREAT M SHOOT OR ACIDIZE AI REPAIR WELL CI (Other)	ULL OR ALTER CASING	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (NOTE: Report results Completion or Recompl t details, and give pertinent dates,	of multiple completion o etion Report and Log form	sing T* X n Well m.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugging operations occurred June 9-17, 1982.

Wash over & pull stuck tubing. Left part of 1 joint and packer in hole. Top of fish approx. 3080'. Set CIBP at 2950' with 20 sxs Class "H" + 2% CaCl2. Mixed & circulated hole with 9.8 ppg salt gel mud. Perforate 4 holes at 1659' to 1660' and 4 holes at 559' to 600'. Squeezed perforations at 1659-60' with 50 sxs Class "H" + 2% CaCl2 (Tagged with tubing at 1490'). Squeezed perforations at 599-600' with 50 sxs Class "H" + 2% CaCl2 (Tagged with sand line at 200'). Run 10 sack plug at surface. Operation observed and approved by Mr. Arlin Coke of USGS. Set P & A monument. Completed reclamation work.

Final Report.

18. I hereby cortify that the foregoing in the and correct SIGNED	TITLE Exec. Vice President	DATE 6/18/82
(This space for Federal on SDP R COVED (Orig. Egd.) PETER W. CHESTER APPROVED BY CONDITIONS OF APPROVAL, IF ANY :	TITLE	DATE
FOR JAMES A. GILLHAM DISTRICT SUPERVISOR	e Instructions on Reverse Side	