

1-10
(May 1983)

NM.O.C.D. *FILE*
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

(Other instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

NM 07781

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Sq. lake-Greyburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

San Andres

25-16-30

12. COUNTY OR PARISH

EDDY

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

ARWOOD LTD. ✓

3. ADDRESS OF OPERATOR

P.O. BOX 8 LOCO HILLS, NM 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

2630' FNL 2630 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SET CEMENT RETAINER 100' ABOVE TOP PERFORATION.

PUMPED WELL VOLUME OF CEMENT PLUS 10 SACKS INTO FORMATION

FILLED WELL BORE WITH MUD TO BASE OF SALT, PERFORATED ABOVE SURFACE SHOE AND SQUEEZED 100' PLUG IN SURFACE.

PUMPED MUD TO 430" and pumped cement to 295' (top salt).

PUMPED 10 SACKS CEMENT PLUG AT SURFACE

CLEANED SURFACE LOCATION AND LEVELED AS PER U.S.G.S. REQUIREMENTS

RIPPED DRILL PAD TO A DEPTH OF 12"

RECEIVED

NOV 03 1980

C. C. D.

ARTESIA, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

B.D. Hope

TITLE

SUPT.

DATE

6-5-79

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) PETER W. CHESTER

TITLE

ACTING DISTRICT ENGINEER

DATE

OCT 24 1980

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side