

C:5F

M. O. C. C. COPY

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 07781

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Loe Federal

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Sq. Lake-Grayburg San Andres

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

30-16-31

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER Infection  
JAN 24 1980

2. NAME OF OPERATOR

Arwood, Ltd.

3. ADDRESS OF OPERATOR

P. O. Box 8 Loco Hills, New Mexico 88255 OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

14. PERMIT NO. 10' FNL 10' FWL

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3870 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to plug and abandon above well in the following manner 45 days from approval.

Set cement retainer 100' above perforation.

Squeeze well bore volume plus 10 sacks into formation.

Pump mud to 1350' and pump cement to 1450'.

Pump mud to 650' and cement to 750'.

Pump mud to surface pump, 10 sacks cement plug at surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

B. D. Hope

TITLE

Supt

DATE

4-12-79

(This space for Federal or State office use)

APPROVED BY (Sig. Sgd.) ALBERT R. STALL  
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE

JAN 23 1980

\*See Instructions on Reverse Side