

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 07781

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LOE ~~XXXXXXXXXX~~

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Sq. Lake-Grayburg San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

30-16-31

12. COUNTY OR PARISH

EDDY

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER INJECTION

2. NAME OF OPERATOR

ARWOOD LTD. ✓

3. ADDRESS OF OPERATOR

P.O. BOX 8- LOCO HILLS, NM 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

10' FNL 10' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3870 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☒ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

INSTILL 4½ CEMENT RETAINER ON WORK STRING. SET RETAINER AT 3126.
TRIED TO SQUEEZE TO 3000 PSI. WOULD NOT SQUEEZE PULL OUT OF RETAINER
SPOT 25 SACKS CLASS "H" PLUG (254') CEMENT. PUMP MUD TO 1450, PUMP
CEMENT TO 1350. PUMP MUD TO 750' AND CEMENT TO 650' BRING MUD TO
SURFACE. DISPLACED MUD AT SURFACE WITH 10 SACKS PLUG.
CLEANED SURFACE LOCATION AND LEVELED AS PER USGS. REQUIREMENTS.
RIPPED DRILL PAD TO A DEPTH OF 12".

RECEIVED

NOV 03 1980

O. C. C.
ARTESIA OFFICE

RECEIVED

JUL 29 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICOPosted 10-2
P & A
11-7-80

18. I hereby certify that the foregoing is true and correct

SIGNED

B D Hope

TITLE SUPERINTENDENT

DATE 7-28-80

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE OCT 24 1980