

30-015-10919

Form 9-331a  
(Feb. 1951)Budget Bureau 42-R358.2  
Approval expires 12-31-52(SUBMIT IN TRIPLICATE)  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Las Cruces  
Lease No. 050249 A  
Unit Brooks

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

\_\_\_\_\_, 1952Well No. Imp. 112 is located 1245 ft. from N line and 235 ft. from W line of sec. 19S. 1/4 Sec. 19 - T. 27N. R. 20E. N.M.

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Empire

(Field)

Doña Ana

(County or Subdivision)

N. Mex.

(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Refer to plan attached to Imp. 112, N.M. to drill  
 112 to drill well with Rotary tools to 100 ft. below the Upper-Seven Rivers  
 pay around 505' and then core the pay zone with the Rotary tools and move on  
 Cable tools and run out the upper 100 ft. of the pay zone. The pay  
 zone will be shot in core and perforated by for a satisfactory  
 water injection rate. When the hole is 100 ft. deep a water string of  
 tubing will be run to the bottom of the hole and the portion of the tubing  
 through the pay zone perforated. The hole will then be filled with pea gravel  
 from the bottom of the hole to the top of the pay zone. Approximately 1' of  
 sand will then be placed on top of the gravel and 2" tubing run to 10' to 15'  
 above the sand and 10 sacks of cement will be pumped through the 2"  
 tubing. The 2" tubing will then be pulled from the well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Alan E. KnauthstoneAddress 212 Foster Bldg.Artesia, N. Mex.By Harold KuseyTitle Agent