

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Yates Petroleum Corp</i>		Lease <i>Jackson HT</i>		Well # <i>2</i>	
Location of Well	Unit <i>71</i>	Section <i>14</i>	Township <i>17</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor <i>Donnell</i>			Type of Equipment <i>Rotary</i>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>11</i>	<i>8 5/8</i>	<i>24 #</i>		<i>1150</i>	<i>Circ</i>
<i>7 7/8</i>	<i>5 1/2</i>	<i>14 #</i>		<i>1500</i>	<i>100 ?</i>
Casing Data:					
Surface <i>53</i> joints of <i>8 5/8</i> inch <i>24</i> # Grade <i>J S</i>					
(Approved) (Rejected)					
Inspected by <i>R. L. Starnes</i> date <i>5-19-67</i>					
Cementing Program					
Size of hole <i>12 1/4</i> Size of Casing <i>8 5/8</i> Sacks cement required					
Type of Shoe used <i>Float</i> Float collar used Btm 3 jts welded <i>Thread Lock</i>					
TD of hole <i>1165</i> Set Feet of <i>8 5/8</i> inch <i>24</i> # Grade <i>J</i>					
New-used csg. @ <i>1165</i> with <i>100</i> sacks neat cement around shoe					
+ <i>500</i> sax <i>Life water</i> additives <i>4% Gel</i>					
Plug down @ <i>2:40</i> (AM) (PM) Date <i>5-20-67</i>					
Cement circulated <i>No</i> No. of Sacks					
Cemented by <i>Denton</i> Witnessed by <i>Starnes</i>					
Temp. Survey ran @ <i>11:30</i> (AM) (PM) Date <i>5-20-67</i> Top cement @ <i>75'</i>					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <i>Ran 1" tbg to 220 feet</i>					

<i>5-21-67 tbg depth</i>	<i>Time</i>	<i>Sax</i>	<i>Calc</i>
<i>210</i>	<i>1:15 PM</i>	<i>100 c</i>	<i>2%</i>
<i>252</i>	<i>5:10 PM</i>	<i>50 c</i>	<i>6%</i>
<i>168</i>	<i>9:10 PM</i>	<i>50 c</i>	<i>6%</i>
<i>"</i>	<i>"</i>	<i>100 c</i>	<i>2%</i>

circ good cmt at end