

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Arwood Ltd. ✓		8. FARM OR LEASE NAME Mulcock Federal	
3. ADDRESS OF OPERATOR Petroleum Building - Tower Suite, Roswell, NM		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FWL, 1650' FSL Sec. 25, T16S, R30E, NMPM		10. FIELD AND POOL, OR WILDCAT Sq. Lake; Gbr, S.A.	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T16S, R30E NMPM	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3813 K.B.		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	PULL OR ALTER CASING	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	MULTIPLE COMPLETE	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ABANDON*	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		<input type="checkbox"/>

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

28' of 14" - Circulated.

748' of 8 5/8", 24# with 150 sx.

3200' of 5 1/2", 14# with 250 sx.

Perfs. 2960'-66, 2998-3006, 3028-40 and 3161-71.

- 1) Spot a 100' plug across perforations.
- 2) Shoot off 5 1/2" casing.
- 3) Spot a 100' plug across stub of pipe.
- 4) Spot a 100' plug across base of salt @ 1640'. A common plug may be used if stub of casing and base of salt are at same depth.
- 5) Spot a 100' plug at shoe of surface.
- 6) Spot a 25' plug and marker at surface.

RECEIVED

APR 30 1975

O. C. C.
ARTESIA, OFFICE

RECEIVED
APR 29 1975
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED J. M. - 13 Aug

TITLE Agent

DATE 4/28/75

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF ~~APPROVAL~~, IF ANY:

~~TITLE~~
~~SUBJECT TO POSSIBLE~~
~~INSTRUMENT THAT PAD AND/OR ROLLS~~
~~STRIPPED AND SEEDS~~

DATE _____

***See Instructions on Reverse Side**

CONTACT THIS OFFICE REGARDING ABOVE
BEFORE MAKING FINAL CLEANUP.

APPROVED

APR 29 1975

R. L. BEEKMAN
ACTING DISTRICT ENGINEER