16.

IITED STATES

SUBMIT IN T' ICATE.

	EOLOGICAL SURVEY	e side)	5. LEASE DESIGNATION NM 0359260	
(Do not use this form for proposa	CES AND REPORTS ON WE is to drill or to deepen or plug back to a drill FOR PERMIT—" for such proposals,)		6. IF INDIAN, ALLOTTER	OR TRIBE NAME
OIL GAS WELL OTHER	RE	CEÏVED	7, UNIT AGREEMENT NA	ME
2. NAME OF OPERATOR JACK L. MCCLELLAN		<u> </u>	8. FARM OR LEASE NAM HARRIS FED	
3. ADDRESS OF OPERATOR BOX 848 - ROSWELL	, NEW MEXICO 88201	"' - 0 13/Z	9. WELL NO.	
4. LOCATION OF WELL (Report location cle See also space 17 below.) At surface	arly and in accordance with any State requ	SIA, OFFICE	WEST HENSH	AW GRAYBUR
2970' FSL & 660'	FEL		11. SEC., T., R., M., OR B SURVEY OR AREA LOT 16 5-16S-30E	VMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc. 3823 G.L.)	12. COUNTY OR PARISH	NEW MEXICO

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:				
TEST WATER SHUT-OFF		PULL OR ALTER CASING	X	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*	X	SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL		CHANGE PLANS		(Other)		
(Other)				(Note: Report results of m Completion or Recompletion	ultiple completion on Well Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

IN JULY 1968 THIS WELL WAS DRILLED TO TD OF 2780' W/PLUGGED BACK DEPTH OF 2777'. PREMIER ZONE PERFORATED 2734-44,2746-52' AND 2757-62'. ACIDIZED W/1,000 GAL. ACID AND FRACED W/20,000 GAL. WATER AND 25,000 LBS. SAND. POTENTIALED 8-2-68 25B0, 5 BW, 150 MCF

IN JULY 1970 PRODUCED A TOTAL OF 5 BO AND 13 BW AND HAS BEEN CLOSED IN SINCE THAT TIME.

Propose to pull $4\ 1/2"$ casing from free-point (1650'-1800') spot cement plug 2600' to 2777'.

50' PLUG IN AND OUT OF TOP OF 4 1/2" CUT OFF CASING. 50' PLUG IN AND OUT OF BASE OF 8 5/8" CASING @ 440' 10 SK PLUG IN TOP OF 8 5/8" CSG.



· · · · · · · · · · · · · · · · · · ·		
18. I hereby certify that the regions is true and correct SIGNED	D	T MARCH 14, 1972
(This space for Federal or State office 1986)		
APPROVED TO APPROVAL, IF ANY:	TITLE	DATE
A 15 1972		
With Zulle	e Instructions on Reverse Side	
ACTING DISTING		