

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

JUN 24 1968

**U. C. C.**  
**ARTESIA, OFFICE**

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Eagle Creek "BL"
3. Address of Operator 207 So. 4th St. - Artesia, New Mexico 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>1650</u> FEET FROM THE <u>West</u> LINE AND <u>990</u> FEET FROM THE <u>South</u> LINE, SECTION <u>23</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.		10. Field and Pool, or Wildcat Undes. Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3500'		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Drilled 9-7/8" hole to 1197'. Reduced to 7-7/8" hole and drilled to 1500' TD. (1492' TD Logger). Ran 38 joints of 7" OD 20#, J-55 SS, 8Rd, ST&C casing to 1192' GL. Cemented with 350 sacks of Incor with 4 cu. ft. Gilsonite, 100# flocele, 7 sacks gel added plus 50 sacks Incor with 2% CaCl. Plug down at 6:15 P.M. (6-14-68). Circulated out approximately 100-150 sacks of cement. After 24 hours cement had fallen back 11' from the surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul White TITLE Engineer DATE 6-18-68  
APPROVED BY W. A. Gressett TITLE Assistant Engineer DATE JUN 24 1968  
CONDITIONS OF APPROVAL, IF ANY: