

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 1. LOCATE
(Other instructions on
reverse side)Form approved
Budget Bureau No. 11-11-11-11

5. LEASE DESIGNATION AND REPORT NO.

LC-064050 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ GAS ☐ OTHER ☐ DRILLING	RECEIVED	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION	AUG 28 1968	8. FARM OR LEASE NAME TRIGG FEDERAL
3. ADDRESS OF OPERATOR BOX 68, HOBBS, N. M. 88240	D. C. C.	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. Also space 17 below.) At surface 1980' FNL x 1980' FWL Sec. 34 (Unit F, SE 1/4 NW 1/4)	ARTESIAN OFFICE	10. FIELD AND POOL, OR WILD CAT WILDCAT
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 34-17-27 NMPM
		12. COUNTY OR PARISH EDDY
		13. STATE NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Noble Drilling Co. spudded 17 1/2" hole 9:30 PM 8-16-68. On 8-17-68, 13 3/8" OD 48" H-40 ST&C casing was set @ 314' w/ 400 sy Incon plus 2% Gel + 100 sy neat + 2% CACL. Cement circulated. WOC 22 hrs. Tested casing 500 psi for 30 minutes. Test O.K.

Reduced hole to 12 1/4" @ 314'. On 8-21-68, 9 5/8" OD 32.3 # H-40 casing was set @ 1599' w/ 1100 sy Incon + 2% Gel + 1000x neat + 2% CACL. Cement circulated. WOC 27 1/2 hrs. Tested casing w/ 1000 psi for 30 min. Test O.K.

Reduced hole to 8 3/4" @ 1599' and resumed drilling

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE AUG 23 1968

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

0-4- USGS-ART
1-NSW
1-SUSP
1-RRY
2-HONDO

AUG 27 1968
R. L. BLUMHART
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side