(May 1963)	IITED STATES	SUBMIT IN T LICAT		red. au No. 42-Ri
	DEPARTMENT OF THE INTER GEOLOGICAL SURVEY	NOR (Other instruction of on verse side)	NM- 03619	and Serial
in intervention	RY NOTICES AND REPORTS	back to a different reservoir.	6. IF INDIAN, ALLOTTH	E OR TRIBE N
	ise "APPLICATION FOR PERMIT-" for such		7. UNIT AGREEMENT N	AME
WELL WELL	OTHER		8. FARM OR LEASE NA	ME
2. NAME OF OPERATOR Yates Petroleum Corporation		Federales	"BO":	
3. ADDRESS OF OPERATOR		· · · · · · · · · · · · · · · · · · ·	9. WELL NO.	
207 South 41	th Street - Artesia, Ne	ew Mexico	1	• • •
4. LOCATION OF WELL (Repo See also space 17 below.	ort location clearly and in accordance with an	y State requirements.*	10. FIELD AND POOL,	
	, W 990' FNL & 990' FWL (	of Sec. 23-175-25	5E Eagle Cree	
TAM TA	A 990 FRE & 990 FRE &		SURVEL OR AND	A .
			Sec. 23-17 Unit D NM	IPM
14. PERMIT NO.	15. ELEVATIONS (Show whether I	DF, RT, GR, etc.)	12. COUNTY OF PARIS	
	3507' GR		Eddy	N.Me
16.	Check Appropriate Box To Indicate	Nature of Notice, Report, o	or Other Data	
NOT	TICE OF INTENTION TO:		SEQUENT REPORT OF :	2 2 4 1
	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING	WELL
TEST WATER SHUT-OFF FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING	CASING .
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	Surface Casi	ENT*
REPAIR WELL	CHANGE PLANS	(Other) Ran 7"	sults of multiple completio	
(Other)		Completion or Rec	completion Report and Log I	(orm.)
17. DESCRIBE PROPOSED OR C proposed work. If w nent to this work.)*	OMPLETED OPERATIONS (Clearly state all pertinvell is directionally drilled, give subsurface lo	cent details, and give pertinent o cations and measured and true v	ertical depths for all mark	ers and zones
		an remperature o	urvey and rou	nu cop
	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 2719	E D	ated to surfa WOC. Filled and drilled pressure for	d cemen ce. to plug 30 min.
	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b>	A surface. Ran K Cement circul 30 AM. 1-21-70. CaCl. WOC 6 hrs Cested with 500# A hole to 6¼" and E D 70 JAN	obe tubing an ated to surfa WOC. Filled and drilled pressure for	d cemer ce. to plug 30 min.
	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce RECEIV JAN 2719	A surface. Ran K Cement circul 30 AM. 1-21-70. CaCl. WOC 6 hrs Cested with 500# A hole to 6¼" and E D 70 JAN	obe tubing an ated to surfa WOC. Filled and drilled pressure for ad resumed dri	d cemer ce. to plug 30 min. lling.
	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 27 19 <b>D.C.C.</b> ARTESIA, DFT	A surface. Ran K Cement circul 30 AM. 1-21-70. CaCl. WOC 6 hrs Cested with 500# A hole to 6¼" and E D 70 JAN	obe tubing an ated to surfa WOC. Filled and drilled pressure for ad resumed dri	d cemer ce. to plug 30 min.
18. I hereby certify that t SIGNED	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 27 19 <b>D.C.C.</b> ARTESIA, DFT	E D	obe tubing an ated to surfa WOC. Filled and drilled pressure for d resumed dri	d cemer ce. to plug 30 min. lling.
18. I hereby certify that t SIGNED	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 27 19 <b>D.C.C.</b> ARTESIA, DFT	E D	obe tubing an ated to surfa WOC. Filled and drilled pressure for d resumed dri	d cemer ce. to plug 30 min. lling.
18. I hereby certify that t SIGNED	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 27 19 <b>D.C.C.</b> ARTESIA, DFT	E D	obe tubing an ated to surfa WOC. Filled and drilled pressure for ad resumed dri	d cemer ce. to plug 30 min. lling.
18. I hereby certify that t SIGNED	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 27 19 <b>D.C.C.</b> ARTESIA, DFT	E D	obe tubing and ated to surfa WOC. Filled and drilled pressure for ad resumed dri	d cemen ce. to plug 30 min. lling.
18. I hereby certify that t SIGNED	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce RECEIV JAN 27 19 D.C.C. ARTESIA, DFT the foregoing is true and correct TITLE_ al or State office use) TITLE_ TITLE_	A surface. Ran K Cement circul 30 AM. 1-21-70. CaCl. WOC 6 hrs Cested with 500# ad hole to 6¼" and CED 70 JAN Geologist	obe tubing and ated to surfa WOC. Filled and drilled pressure for ad resumed dri	d cemer ce. to plug 30 min. lling.
18. I hereby certify that t SIGNED	of cement at 720' from with 475 sx of 4% CaCl Cement in place at 10: surface with 75 sx of at 9:00 PM 1-21-70. T and tested OK. Reduce <b>RECEIV</b> JAN 27 19 <b>D.C.C.</b> ARTESIA, DFT	E D	obe tubing and ated to surfa WOC. Filled and drilled pressure for ad resumed dri	d cemen ce. to plug 30 min. lling.

.

-