

NO. OF COPIES RECEIVED	1
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 18 1971

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**O. C. C.**  
ARTESIA, OFFICE

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Gissler AV
3. Address of Operator 207 South 4th Street - Artesia, New Mexico	9. Well No. 3
4. Location of Well UNIT LETTER <u>E</u> , <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>23</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3511' GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>5 1/2" Csg, Perf. &amp; Sand Frac.</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1450'.

Ran a tapered string of production casing as follows: 970' of 5 1/2" 15.5#, 480' of 4 1/2" 9.5# casing (total of 1450') 1-Float shoe and 4 centralizers cemented with 150 sacks Incor Neat. PD 3:00 P.M. 12-30-70. Cement Circulated

Perforated by Perfojets .45" jets the following intervals: 1307-1309 3 shots, 1331-1332 2 shots; 1333-1342 10 shots; 1370-1371 2 shots; 1386-1387 2 shots; 1393-1400' 8 shots. Total of 27 shots.

Sand Frac'd down casing perforations with 1500 gallons 15% NE acid for breakdown, 20000# 20-40 sand and 80000 gallons of treated water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie L. Gressett TITLE Engineer DATE 1-15-71

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE JAN 18 1971

CONDITIONS OF APPROVAL, IF ANY: