

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPL. E\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 036191

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federales "B0"

9. WELL NO.

2-Y

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 22-17S-25E  
Unit A NMPM

12. COUNTY OR PARISH 13. STATE

Edgy

N. Mex.

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

990' FNL & 440' FEL of Sec. 22-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3520' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Prod. Csg. Perf. Sd Frac XX

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

4-8-71 - TD 1463'. Ran 1451', tapered string production casing, (4½" 9.5# 420') & (5½" 15.5# 1031') of J-55 casing set at 1463' and cemented with 125 sacks of Incor Neat 2% CaCl. Cement Circ. Centralizers on 4½" casing at 1431, 1343, 1251 & 1130'. WOC 18 hrs. Pressure tested casing with 1000# for 30". Held OK.

4-10-71 - LTD 1463'. Perforated by Perfojet Services using 1-shot per/ft (Jet gun) in the following intervals: 1332, 1339½, 1342, 1345, 1347, 1352, 1358, 1363, 1365, 1367, 1376, 1378, 1380, 1386, 1388, 1401 and 1404'.

4-12-71 - Sand Frac'd by Dowell using 2000 gallons of 15% NE acid for breakdown, 35000# 20-40 sand and 80000 gallons of treated water.

RECEIVED

APR 22 1971

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

Engineer

DATE

4-22-71

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD PURPOSES  
APR 22 1971

Date

ACTING District Engineer

\*See Instructions on Reverse Side