

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 6 1971

O.C.C.
ARTESIA, NEW MEXICO

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name J Lazy J
3. Address of Operator 207 South 4th Street - Artesia, New Mexico 88210		9. Well No. 3
4. Location of Well UNIT LETTER <u>G</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.		10. Field and Pool, or Wildcat Unit. Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3526' GL		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-23-71 - Spudded 13 3/8" hole at 12:30 P.M. 4-23-71.

Drilled to 133' and ran 122' of 10 3/4" 32# J-55 casing set at 133' with 50 sxs Neat 4% CaCl cement and 1-yard of Ready Mix. Cement circulated. PD 4:00 PM 4-23-71. WOC 3 hrs. Reduced hole to 9 7/8" and resumed drilling.

4-30-71 - TD 1136'. Ran 1120' of 7" 23# N-80 casing, 1-Tex Pattern shoe and set at 1133' with 300 sacks of Incor Mix 2% gel, 2% CaCl, 6% gilsonite and 900# cellophane, followed with 100 sacks Neat 2% CaCl cement. Cement circulated. PD 9:00 P.M. 4-30-71. WOC 18 hrs. Drilled out from under shoe and pressure tested casing with 500#. Held OK. Reduced hole to 6 1/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie M. Lutz TITLE Engineer DATE 5-6-71

APPROVED BY W. A. Gressitt TITLE OIL AND GAS INSPECTOR DATE MAY 6 1971

CONDITIONS OF APPROVAL, IF ANY: