

NO. OF COPIES RECEIVED	1
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 19 1971

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**O. C. C.**

ARTESIA, OFFICE

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		5. State Oil & Gas Lease No.
3. Address of Operator 207 South 4th Street - Artesia, New Mexico		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>I</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.		8. Farm or Lease Name J Lazy J
		9. Well No. 4
		10. Field and Pool, or Wildcat Eagle Creek S.A.
15. Elevation (Show whether DF, RT, GR, etc.) 3516' GL		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☒ Perforate & Sand Frac  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-6-71 (TD 1470 (DTD) 1476' (LTD).

Ran a tapered string of production casing as follows: 515.30' of 4½" 9.5# J-55 and 945.71' of 5½" 15.5#, J-55 casing (Total of 1461.01'), 1-Shoe set at 1475' with 125 sxs Incor Neat cement. PD 6:00 P.M. 5-7-71. Cement circulated. Centralizers at 1430, 1340, 1248, 1094'. WOC 24 hrs and pressure tested casing with 1000#. Held OK.

Perforated by Perfojets using .375 jets in the following intervals: 1437, 1417½, 1408, 1396½, 1386, 1378, 1364½, 1353, 1343, 1326, 1330½, 1350, 1363, 1370, 1381, 1399, 1421½. Total 17 holes. Sand Frac'd by Dowell using 2000 gallons of acid for breakdown, 40000# 20-40 sand and 80000 gallons of treated water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rayton Yates

TITLE Engineer

DATE 5-19-71

APPROVED BY W. A. Grissett

TITLE OIL AND GAS INSPECTOR

DATE MAY 21 1971

CONDITIONS OF APPROVAL, IF ANY: