

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

APR 23 1971

O. C. C.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Gissler AV
3. Address of Operator 207 South 4th Street - Artesia, New Mexico	9. Well No. 7
4. Location of Well UNIT LETTER <u>M</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>23</u> TOWNSHIP <u>17S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Unit Eagle Creek S.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3505' GR	12. County Edgy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1160'. Reduced hole at 860' to 9" and drilled to TD of 1160'. Ran 1150' of 7" 23# J-55 and N-80 casing set at 1160' with 750 sxs of cement. Centralizers at 1022, 723, baskets at 808 and 681'. Washed bridge at 455' to 480' and 1060-1160'. Cemented with 300 sxs Incor mix and 150 sxs Neat 2% CaCl, preceded with 2 bags of flocele. PD 12:15 PM 4-16-71. WOC 7 hrs. Ran Temperature Survey and found top of cement at 500'. Fell back to 650'. Good cement at 700' to total depth. Ran 1" and washed bridge from 425 to 447'. Spotted 75 sacks Incor Mix 4% CaCl at 445'. WOC 3 hrs, tagged cement at 317'. Spotted 75 sacks Incor mix 4% CaCl at 315'. WOC 4 hrs., tagged cement at 297'. Spotted 75 sacks Neat 4% CaCl at 295'. WOC 2½ hrs, tagged cement at 253'. Spotted 75 sacks Neat 4% CaCl at 210'. Water 100' from surface. Filled hole with 3¼ yards of Ready-Mix. Cement circulated. Used 450 sacks of Incor Mix 4% CaCl (2700# gilsonite, 1450# flocele and 900# gel), 300 sxs Neat 2% & 4% CaCl. WOC 24 hours. Drilled out plug, tested casing with 500# pressure for 30 minutes. Tested OK. Reduced hole to 6 1/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Edwin L. Gussert TITLE Engineer DATE 4-23-71

APPROVED BY W.A. Gussert TITLE Engineer DATE 4-23-71

CONDITIONS OF APPROVAL, IF ANY:

APR 29 1971