

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR  
(Other Instructions  
reverse side)CATE\*  
on re-Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM 036191

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federales BO

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT  
Eagle Creek S.A.11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA  
Sec. 22-17S-26E  
Unit B NMPM12. COUNTY OR PARISH 13. STATE  
Eddy N. Mex.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓
3. ADDRESS OF OPERATOR  
207 South 4th Street- Artesia, New Mexico 88210
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface 990' FNL and 1650' FEL of Sec. 22-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3528' GL

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).\*

5-9-71 - TD 1149'.

Ran 33 jts of 7" 20# & 23# J-55 & N-80 casing (1136') and set at 1149' with 700 sacks of cement consisting of 700# gel, 2100# gilsonite and 1100# flocele. Cemented with 250 sxs Incor Mix & 50 sxs Neat 2% CaCl. PD 8:30 PM 5-9-71. Baffle collar at 1110', centralizers at 1022, 737' and baskets at 705 & 641'. WOC 3 hrs. and ran 1" tubing. Washed from 520-605'. Spotted 50 sxs Incor Mix 4% CaCl at 605'. PD 12:30 AM 5-10-71. WOC 6 hrs. Ran Temp. Survey, found top of cement at 610-680' and 800' To TD. Ran 1" tubing, unable to wash below 540'. Spotted 50 sxs Incor Mix 4% CaCl at 540'. PD 7:00 AM 5-10-71. WOC 3½ hrs. Tagged cmt. at 500', spotted 50 sxs neat 4% CaCl. PD 11 AM 5-10-71. WOC 2½ hrs. Tagged cmt at 475', spotted 75 sxs Neat 4% CaCl 2/25# flocele. PD 1:45 PM 5-10-71. WOC 2 hrs, tagged cement at 475', spotted 75 sx w/25# flocele, Neat 4% CaCl. PD 4 PM 5-10-71. Bradenheaded 50 sxs Neat 4% CaCl at 5:30 PM. WOC 3 hrs and Bradenheaded 50 sxs Neat 4% CaCl. Ran Temp. Survey, good cement 475-520'. 600-680'800-TD. WOC 1½ hrs and filled hole with 4 yards of Ready-Mix. PD 10 PM 5-10-71. WOC 26 hrs, press tested csg with 400# . OK. Drilled out shoe and pres. tested csg with 300# OK. Reduced hole to 61/8" & resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Eddie L. Haly*

TITLE

Engineer

DATE

5-21-71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DATE

MAY 24 1971

ACCEPTED FOR RECORD PURPOSES

MAY 21 1971

Date

ACTING District Engineer

\*See Instructions on Reverse Side O. C. C.  
ARTESIA, OFFICE