NO. OF COMES RECEIVED 3						Form C-103 Supersedes Old			
DISTRIBUTION  SANTA FE		RECEIVED  NEW MEXICO OIL CONSERVATION COMMISSION				G-102 and C-103 Effective 1-1-55			
FILE	1							·	
LANC OFFICE			301/	1 7 1971	50	J. Indicate T		se : Pec 📶 :	
OPERATOR			n	. C. C.	1	. State Off 6			
			ARTE	SIA, OFFICE	<u> </u>	<del></del>		kalakakakakakakaka ,	
SUNDRY NOTICES AND REPORTS ON WELLS  100 NOT USE THIS FORM FOR PROPOSALS TO BRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)									
	AS CLL	OTHER.	<i>j</i>			Unit Agrees		,	
Augus Petroleum Corporation /						ingena Jackson W			
207 South 4th Street - Artesia, New Mexico 88210						2			
UNIT LETTER D 990 FEET FROM THE NORTH LINE AND 990 FEET FROM						Bagle Creek S.A. 4nd			
THE West LINE, SECTION 26 TOWNSHIP 17S RANGE 25E NMPM									
15. Elevation (Show whether DF, RT, GR, etc.) 3502 GL						2. County Eddy			
16.	Check /	Appropriate Box T	o Indicate N	ature of Notice, Repo	rt or Other	Data		******	
NO.		TENTION TO:		•	EQUENT R		F:		
PERFORM REMEDIAL WORK		PLUG AN	D ABANDON	REMEDIAL WORK		<b>A</b> 1 *	TERING CASI		
TEMPORARILY ABANDON				COMMENCE DRILLING OPNS.	A		IG AND ABAN	<del></del>	
PULL OR ALTER CASING		CHANGE	PLANS	CASING TEST AND CEMENT JOS	. 🔯				
				OTHER	***************************************				
OTHER									
17. Describe Proposed or work) SEE RULE 110	Completed Op	erations (Clearly state o	ıll pertinent deta	ils, and give pertinent dates,	including est	imated date	of starting	any proposed	
5-20-71 -	Spudde	d 4:00 PM 5-	20-71.						
5-20-71 - Spudded 4:00 PM 5-20-71.  Drilled 13 3/4" jole to 251'. Ran 212' of 10 3/4" 32# J-55 csg									
				80 sxs Neat 49				_	
								•	
to pit. PD 12:30 PM 5-21-71. WOC 8 hrs, drilled plug, reduced hole to 9 $7/8$ " and resumed drilling.									
Drilled 9 7/8" hole to 1165'. Ran 1153' of 7" $20\%$ & $23\%$ J-55									
	casing with 1-Tex Pattern Shoe and centralizers at 1035,820 & 689								
	Cemented with 350 sxs at 1165' RT. 200 sxs Incor mix (600 m								
	flocele & 1800# gilsonite) 2% CaCl followed w/100 sxs Incor hear								
	2% CaCl. PD 11:00 AM 7-21-71. Cement did not come to surface.								
	WOC 8 hrs, ran Temperature Survey, found top of cement at 230'								
from surface. Bradenheaded 50 sxs Incor mix 4% CaCl. Hole filled									
	to sur	face. PD 8:	15 PM 5-	21-71. WOC 18	hrs, p	ressur	e test	:eđ	
				Drilled plug					
	casing	shoe. Held	OK. Re	duced hole to	6¼" and	resum	ed äri	.lling.	
18. I hereby certify that th	e information	above is true and compl	ete to the best o	f my knowledge and belief.					
SIGNED Eddic	In la	integral	TITLE E	ngineer		DATE	6-4-71	L	
1 /		7 "						4074	
APPROVED BY	1. B	ressett	TITLE	IL AND GAS INSPECTOR		DATE J	UN 7	197 <b>1</b>	

CONDITIONS OF APPROVAL, IF ANY: