

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>Ingram Jackson 26</i>		Well # <i>3</i>	
Location of Well	Unit <i>B</i> <i>99th</i>	Section <i>27</i>	Township <i>17</i>	Range <i>25</i>	County <i>El Paso</i>
Drilling Contractor <i>Cactus Drilling Co.</i>			Type of Equipment <i>Rotary</i>		
APPROVED CASING PROGRAM <i>approved 5-24-71</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>10 3/4" x 15"</i>	<i>10 7/8" x 15"</i>	<i>32</i>		<i>210</i>	<i>one</i>
<i>9 7/8"</i>	<i>7"</i>	<i>23 or 26</i>		<i>1150</i>	<i>"</i>
<i>6 1/8"</i>	<i>4 1/2" x 5 1/2"</i>	<i>430' 1050'</i> <i>9.5 + 14.5</i>		<i>1500</i>	
Casing Data: <i>10 3/4" - 257-gr. 80</i>					
Surface <i>29</i> joints of <i>7</i> inch <i>26</i> # Grade <i>N-80</i>					
(Approved) (Rejected)					
Inspected by <i>Ch. Howe</i>			date <i>5-25-71</i>		
Cementing Program					
Size of hole <i>9 7/8"</i>		Size of Casing <i>7"</i>		Sacks cement required	
Type of Shoe used <i>Super Bottom</i>		Float collar used <i>no</i>		Btm 3 jts welded <i>Inner Leg</i>	
TD of hole <i>1166 DF</i> Set <i>1153</i> Feet of <i>7</i> Inch <i>26</i> # Grade <i>N80</i>					
Use used csg. @ <i>1153 gr.</i> with <i>350</i> sacks neat cement around shoe					
+ <i>sax</i> additives <i>2700</i>					
Plug down @ <i>8:45</i> (AM) (PM) Date <i>5-26-71</i>					
Cement circulated <i>yes</i>		No. of Sacks <i>65 sacks</i>			
Cemented by <i>Denton</i>		Witnessed by <i>Gressett & Howe</i>			
Temp. Survey ran @		(AM) (PM) Date		top cement @	
Casing test @		(AM) (PM) Date			
Method Used		Witnessed by			
Checked for shut off @		(AM) (PM) Date			
Method used		Witnessed by			
Remarks:					