

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME S.W. Henshaw Premier Unit
2. NAME OF OPERATOR Kennedy Oil Co., Inc.		8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR Box 151 Artesia, New Mexico 88210		9. WELL NO. 16
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL 660' FSL Sec. 18, T-16S, R-30E NPM		10. FIELD AND POOL, OR WILDCAT Henshaw Grayburg, West
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18, T-16S, R-30E NPM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3761 GR 3770 KB		12. COUNTY OR PARISH Eddy
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Casing Change of plans	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/24/71 Ran 30' of 12 3/4" conductor casing, set at 35', with 1 1/4 yards cement.

CHANGE OF PLANS:

6/26/71 Spudded well and ran 409' GR of 8 5/8", 32# casing, and cemented with 115 sx. of cement, which included 65 sx. of Dowell Light Wt. cement with a 1.54 slurry yield, and tailed in with 50 sx. of Dowell expanding cement with a 1.18 slurry yield and a 500 # compressive strength in 5 hr's. WOC 18 hr's. Tested and held 700 psi for 30". Resumed drilling 6/27/71.

The above change was made with verbal permission from the USGS 6/25/71.

Propose to cement 5 1/2" 14# production casing with 350 sx. of Dowell expanding cement, which is calculated to bring the cement into the salt section, which is a change of original plans to circulate cement.

RECEIVED

JUN 30 1971

O. C. C.

ARTESIA, OFFICE

RECEIVED
JUN 29 1971
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED R. B. Beekman

TITLE V.P.

DATE 6/28/71

(This space for Federal or State office use)

TITLE

DATE

APPROVED

JUN 29 1971

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.