

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>YATES PET. CORP.</u>		Lease <u>JACKSON EST. BY</u>		Well # <u>2</u>	
Location of Well	Unit ^F <u>23 1/2 N</u> <u>23 1/2 W</u>	Section <u>22</u>	Township <u>17</u>	Range <u>25</u>	County <u>EDDY</u>
Drilling Contractor <u>CACTUS DRILL CO.</u>			Type of Equipment <u>POTARY</u>		
APPROVED CASING PROGRAM <u>6-24-71</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>13 3/8"</u>	<u>10 3/4"</u>	<u>32</u>		<u>210'</u>	<u>CIRC</u>
<u>9 7/8"</u>	<u>7"</u>	<u>23</u>		<u>1150'</u>	<u>"</u>
<u>6 1/8"</u>	<u>4 1/2" + 5 1/2"</u>	<u>9.5 + 14"</u>		<u>1500'</u>	<u>"</u>
Casing Data:					
Surface <u>29</u> joints of <u>7"</u> inch <u>23</u> # Grade <u>J-55 + N-80 API</u> <u>APP.</u> (Approved) (Rejected)					
Inspected by <u>D. J. Howe</u> date <u>7-3-71</u>					
Cementing Program					
Size of hole <u>9 7/8"</u> Size of Casing <u>7"</u> Sacks cement required <u> </u>					
Type of Shoe used <u>TEXAS</u> Float collar used <u> </u> Btm 3 jts welded <u>THREAD-LOCK</u>					
TD of hole <u> </u> Set <u>1142</u> Feet of <u>7</u> Inch <u>23</u> # Grade <u>J-55 API</u>					
New-used csg. @ <u>1142</u> with <u>250</u> sacks neat cement around shoe + <u>100 MIA</u> additives <u>2% CPT. CLOR. 2% BILSONITE.</u>					
Plug down @ <u>1"</u> (AM) (PM) Date <u>7-5-71</u>					
Cement circulated <u>NO</u> No. of Sacks <u> </u>					
Cemented by <u>DENTON</u> Witnessed by <u>D. J. Howe</u>					
Temp. Survey ran @ <u>1130</u> (AM) (PM) Date <u>7-5-71</u> top cement @ <u>640'</u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u> </u>					

510' - 10 3/4 Csg. 40# API 500 P.M. 7-3-71
CENT. - 1012' - 795' - 7" - 175 SX CIR.
RAN 4 YARDS READY TO FARM SURFACE
BENNETT TAGGED PLUG 1076'
HAD PUMP PRESSURE 7 200-250" WHILE CEMENTING.
POSSIBLE TOP 7 CEMENT 390'