

N. M. O. C. C. COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR  
(Other instructi  
verse side)CATE\*  
on re-Copy 7 SF  
Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Yates Petroleum Corporation		8. FARM OR LEASE NAME Federal BZ
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, New Mexico 88210		9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 330' FEL Sec. 21-17S-25E		10. FIELD AND POOL, OR WILDCAT Eagle Creek S.A.
14. PERMIT NO.		11. SEC. T. R. M. OR BLE. AND SURVEY OR AREA Sec. 21-17S-25E Unit P NMMP
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3551' GL		12. COUNTY OR PARISH Eddy
		13. STATE N. Mex.

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

4 1/2" &amp; 5 1/2" Prod. csq.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1534' - Ran a tapered string of production casing as follows: Ran 556' of 4 1/2", J-55 and 962' of 5 1/2" 14#, J-55 casing (Total 1518'), 1-shoe and float collar, set at 1534' with 125 sacks of Incor Neat 2% CaCl cement. Cement circulated. PD 4:30 PM 7-19-71. Centralizers at 1491, 1372, 1255, and 1089'. WOC 24 hours and pressure tested casing with 1000#. Held OK.

Perforated by Dresser Atlas as follows: 1255, 1294 1/2, 1305 1/2, 1316, 1328, 1338, 1352 1/2, 1371 1/2, 1389, 1417, 1462 1/2, 1492 1/2, 1286 1/2, 1299 1/2, 1312, 1321, 1324, 1334 1/2, 1342, 1345, 1361 1/2, 1374 1/2, 1382 1/2, 1477 1/2, 1523 1/2, 1312, 1330, 1336 1/2, 1347, 1359'.

Sand Frac'd with 9000 gallons 15% acid for breakdown, 40000# 20-40 sand and 80000 gallons of treated water.

RECEIVED

AUG 2 1971

O. C. C.  
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

7-29-71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES  
JUL 30 1971  
Date  
ACTING District Engineer

\*See Instructions on Reverse Side