

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
FEB 13 1992

O. C. D.
OFFICE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
NM 0439900

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Federal CB #1

9. API Well No.
30-015-20489

10. Field and Pool, or Exploratory Area
Eagle Creek SA

11. County or Parish, State

Eddy, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other P&A

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N, 330' FSL, 2310' FWL, Sec. 15-17S-25E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged and abandoned well as follows:

Notified BLM, Carlsbad, NM of plan to start so they could witness job.

RUPU. Lay down 54 5/8" rods and pump. Install BOP and TOOH with 46 jts 2-3/8" tubing.

RIH with tubing to 1250' and spot 25 sx Class "C" plug w/2% CaCl. Shut in overnight.

Tagged top of cement at 939'. Actual bottom plug from 1248-939'. Circulate hole with 18

BMLF. Laid down 16 joints tubing and put bottom at 460; Mixed 25 sx Class "C" cement and

displace with .9 BMLF. Second plug from 460-219'. Laid down 13 joints tubing and 10'

sub. Put bottom at 77'. Mixed 10 sx Class "C" and circulate to surface. Laid down sub

and 2 joints. Flushed line and cleaned BOP. RD and move out rig and P&A equipment.

Cut off wellhead and anchors. Installed dry hole marker.

Work began 1-29-92 and completed 1-30-92.

Post ID-2
2-14-92
P&A

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

[Signature]

Title Production Supervisor

Date 2-3-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ENGINEER

Date

2/10/92