

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP-CATE*
(Other Instructional
verse side)Form approved.
Budget Bureau No. 42-R1421-13

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 0219603
2. NAME OF OPERATOR Yates Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, New Mexico 88210		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 1650' FEL of Section 21-17S-25E		8. FARM OR LEASE NAME Federal BZ
14. PERMIT NO.		9. WELL NO. 4
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3558' GL		10. FIELD AND POOL, OR WILDCAT Eagle Creek S.A.
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 21-17S-25E Unit 0 NMPM
		12. COUNTY OR PARISH Eddy
		13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐4½" & 5½" Prod. Casing ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 1512' - Ran a tapered string of production casing as follows: Ran 485' 11#, J-55 and 1009' of 5½" 14#, J-55 (Total 1494'), 1-float collar and shoe, set at 1512' with 125 sacks of Incor Neat 2% CaCl cement. Cement circulated. PD 4:00 PM 8-29-71. WOC 24 hours and tested casing with 1000# pressure. OK.

Perforated by Perfojet Services as follows: 1502½, 1493½, 1378, 1354, 1342½, 1338, 1329, 1326½, 1322, 1320, 1312½, 1310, 1429½, 1457, 1390½, 1380, 1324½, 1317½, 1315, 1293, 1335½, 1333½, 1331, 1320, 1322, 1324, 1326 and 1328.

Sand Frac'd using 6000 gallons of 15% Regular Acid for breakdown, 40000# 20-40 sand and 80000 gallons of treated water.

RECEIVED
SEP 16 1971
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Eddie M. Beekman

TITLE

Engineer

DATE

9-16-71

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

SEP 16 1971

H. L. BECKMAN

ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side