

N. M. O. C. C. COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
SUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0219603

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal BZ

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Eagle Creek S.A.

11. SEC., T., R., M., OR B.L. AND  
SURVEY OR AREASec. 28-17S-25E  
Unit B NMPM

12. COUNTY OR PARISH

13. STATE

Eddy

N. Mex.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

990' FNL &amp; 1650' FEL of Sec. 28-17S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3558' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 4½" &amp; 5½" Prod. casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1504'; PBTD 1494' - Ran a tapered string of production casing as follows: Ran 473' of 4½" 11#, J-55 & 1008' of 5½" 14#, J-55 casing (Total 1481') 1-float collar and guide shoe, set at 1494' with 125 sacks Incor Neat 2% CaCl. Cement circulated. PD 4:30 PM 9-1-71. WOC 24 hours and tested casing with 1000# pressure. Tested OK. Perforated by Perfojets: 1387, 1380, 1377, 1373, 1371½, 1361, 1356½, 1350½, 1346½, 1343½, 1333½, 1318½, 1391½, 1382, 1374½, 1353, 1345, 1336, 1330½, 1320½, 1316, 1369, 1363½, 1359. Sand Frac'd using 6000 gallons 15% regular acid, 40000# 20-40 sand and 80000 gallons of treated water.

RECEIVED

SEP 17 1971

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

RECEIVED

SEP 20 1971

O. C. C.  
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

9-17-71

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

SEP 12 1971

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side