

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI-AD*
(Other instructions on re-
verse side)Form approved,
Budget Bureau No. 42-11421.

5. LEASE DESIGNATION AND SERIAL NO.

NM 12832

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal CD

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Eagle Creek S.A.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 28-17S-25E
Unit C NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3567' GL

12. COUNTY OR PARISH

Eddy

13. STATE

N.Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Spud & set 10 3/4" csg. X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-30-71 - Spudded 1:30 PM 9-30-71.

TD 150' - Drilled a 13 3/4" hole to 150' and ran 4 jts. of 10 3/4" 32#, J-55 csg. set at 150' w/75 sx Incor Neat 4% CaCl. PD 4:30 PM 9-30-71. Cement circ. WOC 7 hrs and drilled shoe, reduced hole to 9 7/8" and resumed drilling.

TD 1091'. Ran 34 jts of 7" 23#, J-55 & 20# H-40 csg. (Total 1091'), washed in last 8 jts. Landed csg. at 1091' & cmtd w/550 sx. 200 sx Incor Mix (60# flocele 1200# gilsonite & 2 sx hulls) 2% CaCl & 100 sx Incor Neat 2% CaCl. PD 7:45 AM 10-3-71. WOC 6 1/2 hrs. Ran 1" tubing to 700'. Spotted 75 sx Incor Neat 4% CaCl. PD 4:00 PM 10-4-71. WOC 3 1/2 hrs, ran 1" tubing to 700', spotted 75 sx Incor Neat 4% CaCl w/1 sx hulls. PD 8:00 PM 10-4-71. WOC 2 1/2 hrs. Tagged firm cement at 682', spotted 50 sx Incor Neat 4% CaCl, at 676'. Laid down 1" tubing and pumped 50 sx Incor Neat 4% CaCl, filled hole w/5 yrd of Ready-Mix. Job Completed midnight 10-4-71. WOC 4 hrs. Ran Temp. Spud, good cmt 520-TD. WOC 22 hrs tested casing with 500#. OK. Drilled shoe and tested casing to 400# OK. Reduced hole to 6 1/4" and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

10-22-71

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side